

Nadura Tiles

NESO ECLIPSE GREY



Water resistance
High



Colour
Eclipse Grey

Neso is a luxurious Nadura floor that brings depth and character to any space. The dark Eclipse Grey hue is both sophisticated and calming, offering a timeless look.



Specification

GENERAL

Type of floor	Nadura Tiles
Light/dark	Dark
Pattern	Tile
Locking system	Välinge 5G® Dry™
Core	HDF
Bevel	Decorative groove
Colour	Eclipse Grey

DIMENSIONS

Width	280 mm
Width (ISO 24337)	11"
Length	582 mm
Length (ISO 24337)	22.9"
Thickness	10.5 mm
Thickness (ASTM F387)	0.41"
Thickness of wear layer	0.4 mm
Thickness of wear layer (ASTM F410)	.01"
Weight per m²	22 lbs

PACKAGE

Quantity in box	8 pcs
m² / box	1.3
sq.ft per box	13.99 sqft
m² per pallet	70.4 m²
sq.ft per pallet	758 sqft
Weight per m²	10 kg
Weight per box	13 kg
Weight per box	28.6 lbs

CLASSIFICATION AND SAFETY

Supports Underfloor Heating	Yes
Water resistance	High
Thermal conductivity (EN 12664)	0,16 W/(m*K)
Thermal resistance (EN 12667)	R<0.10 (m2 x K)/W
Formaldehyde emission (EN 717-1)	E1(<0.05ppm)
Impact resistance (EN 17142)	>20N small ball, >1600 mm big ball
Thickness swelling (EN 17142)	<8% (6% typical)
Wear resistance (EN 17142)	AC6
CE Marked	Yes
Limited warranty (public environment)	10 years
Limited warranty (home environment)	Limited Lifetime Warranty
Level of use domestic (EN ISO 10874)	Class Very Heavy Residential (Class 23)
Level of use commercial (EN ISO 10874)	Class Very Heavy Commercial (Class 34)

MISC.

Surface texture	Soft Slate
-----------------	------------



Bjelin Sweden AB bjelin.com support@bjelin.se +46-771-101099

Copyright 2025 Bjelin Sweden AB. Weights and dimensions may have minor variations depending on external circumstances. Bjelin reserves the right to deviate from the weight and dimensions in this technical data sheet. Technologies mentioned may be subject to patent protection and invented by Välinge Innovation AB (www.valinge.se/patents). Use of trademarks herein owned by Bjelin Sweden AB or Välinge Innovation AB is under license.



For installation and caring instructions, and further product information, scan the QR code or visit bjelin.com.