

# Nadura Tiles

## LUNA DEW GREY



Water resistance  
High



Colour  
Dew Grey

Luna is a contemporary Nadura floor that brings a fresh, modern touch. The soft Dew Grey colour enhances the room with a sense of openness and tranquillity, offering a refined, airy atmosphere that complements minimalist interiors.



### Specification

| GENERAL        |                   |
|----------------|-------------------|
| Type of floor  | Nadura Tiles      |
| Light/dark     | Light             |
| Pattern        | Tile              |
| Locking system | Välinge 5G® Dry™  |
| Core           | HDF               |
| Bevel          | Decorative groove |
| Colour         | Dew Grey          |

| DIMENSIONS                          |         |
|-------------------------------------|---------|
| Width                               | 280 mm  |
| Width (ISO 24337)                   | 11"     |
| Length                              | 582 mm  |
| Length (ISO 24337)                  | 22.9"   |
| Thickness                           | 10.5 mm |
| Thickness (ASTM F387)               | 0.41"   |
| Thickness of wear layer             | 0.4 mm  |
| Thickness of wear layer (ASTM F410) | .01"    |
| Weight per m²                       | 22 lbs  |

| PACKAGE          |            |
|------------------|------------|
| Quantity in box  | 8 pcs      |
| m² / box         | 1.3        |
| sq.ft per box    | 13.99 sqft |
| m² per pallet    | 70.4 m²    |
| sq.ft per pallet | 758 sqft   |
| Weight per m²    | 10 kg      |
| Weight per box   | 13 kg      |
| Weight per box   | 28.6 lbs   |

| CLASSIFICATION AND SAFETY              |                                         |
|----------------------------------------|-----------------------------------------|
| Supports Underfloor Heating            | Yes                                     |
| Water resistance                       | High                                    |
| Thermal conductivity (EN 12664)        | 0,16 W/(m*K)                            |
| Thermal resistance (EN 12667)          | R<0.10 (m2 x K)/W                       |
| Formaldehyde emission (EN 717-1)       | E1(<0.05ppm)                            |
| Impact resistance (EN 17142)           | >20N small ball, >1600 mm big ball      |
| Thickness swelling (EN 17142)          | <8% (6% typical)                        |
| Wear resistance (EN 17142)             | AC6                                     |
| CE Marked                              | Yes                                     |
| Limited warranty (public environment)  | 10 years                                |
| Limited warranty (home environment)    | Limited Lifetime Warranty               |
| Level of use domestic (EN ISO 10874)   | Class Very Heavy Residential (Class 23) |
| Level of use commercial (EN ISO 10874) | Class Very Heavy Commercial (Class 34)  |

| MISC.           |            |
|-----------------|------------|
| Surface texture | Soft Slate |



**Bjelin Sweden AB**   [bjelin.com](https://bjelin.com)   [support@bjelin.se](mailto:support@bjelin.se)   +46-771-101099

Copyright 2025 Bjelin Sweden AB. Weights and dimensions may have minor variations depending on external circumstances. Bjelin reserves the right to deviate from the weight and dimensions in this technical data sheet. Technologies mentioned may be subject to patent protection and invented by Välinge Innovation AB ([www.valinge.se/patents](https://www.valinge.se/patents)). Use of trademarks herein owned by Bjelin Sweden AB or Välinge Innovation AB is under license.



For installation and caring instructions, and further product information, scan the QR code or visit [bjelin.com](https://bjelin.com).