

# Hardened Wood 2.0

## HARDENED OAK LOSHULT 2.0



### Specification

#### GENERAL

Type of floor	Hardened wood
Type of wood	Oak
Grading	Select
Surface finishing	Matt lacquer
Staining	Light
Light/dark	Light
Pattern	Plank
Locking system	Välinge 5G@
Core	HDF

#### DIMENSIONS

Format	XXL
Width	273 mm
Length	2378 mm
Thickness	11 mm
Thickness of wear layer	0,6 mm

#### PACKAGE

Quantity in box	3 pcs
m <sup>2</sup> / box	1,95 m <sup>2</sup>
Weight per box	21,45 kg

#### CLASSIFICATION AND SAFETY

Light Reflection Value (LRV)	34,6
Supports Underfloor Heating	Yes
Water resistance	Medium
Brinell hardness (EN 1534)	8,2 N/mm <sup>2</sup>
FSC	FSC Mix
SundaHus	Evaluated by SundaHus
Svanen	No
CE Marked	Yes
Limited warranty	30 years



woodura®

**Bjelin Sweden AB** | [bjelin.com](http://bjelin.com) | [support@bjelin.se](mailto:support@bjelin.se) | +46-771-101099

Copyright 2024 Bjelin Sweden AB. Weights and dimensions may have minor variations depending on external circumstances. Bjelin reserves the right to deviate from the weight and dimensions in this technical data sheet. Technologies mentioned may be subject to patent protection and invented by Välinge Innovation AB ([www.valinge.se/patents](http://www.valinge.se/patents)). Use of trademarks herein owned by Bjelin Sweden AB or Välinge Innovation AB is under license.



*For installation and caring instructions, and further product information, scan the QR code or visit [bjelin.com](http://bjelin.com).*