

# Rigid Core

## PLANKS NAPA FROSTY WHITE

Motif  
Lames

Napa, inspiré par le design scandinave, se distingue en tant que l'un de nos best-sellers, insufflant une impression de légèreté et de fraîcheur dans votre espace. C'est un choix idéal pour ceux qui désirent mettre en avant un style marqué de lignes épurées, une palette de couleurs neutres, et une sensation d'espace.



### Spécification

#### GÉNÉRAL

Finition	UV cured acrylic
Colour	Frosty white
Motif	Lames
Système de d'assemblage	5G Dry
Âme centrale	SPC - Rigid polymeric core
Micro-chanfrein	4 sided micro bevel

#### DIMENSIONS

Largeur	228 mm
Longueur	1830 mm
Épaisseur	6.5 mm
Épaisseur de la couche d'usure	20 mil (0,55 mm)

#### EMBALLAGE

Nombre d'articles par paquet	5
Surface (m²) par paquet	2,09 m²
m² par palette	100,2 m²
Poids par m²	9,13 kg
Poids par paquet	19,7 kg

#### CLASSEMENT ET SÉCURITÉ

Greenguard Gold	Greenguard Gold Certified
A+	Yes
Dimensional stability (ISO 23999)	Pass - max < 0.2%/linear ft (305 mm)
Curling (ISO 23999)	Pass - <1 mm
Effect of Castor Chair (ISO 4918)	Pass - 25 000 rev
Coefficient de friction electro-static (ASTM D2047)	Sec : >0,6
Flux radiant critique (ASTM E648)	Classe 1 : ≥ 0,45 W/cm²
Durabilité – COV	Certifié Greenguard Gold
Phtalates et métaux lourds	Phtalates et métaux lourds sous la limite de détection
Indice de transmission sonore (ASTM F90)	54
Indice d'isolation contre les chocs	53
Transmission sonore réduite (ASTM E2179)	20

#### MISC

Water Resistance	High
Construction	SPC - Rigid polymeric core - modular resilient flooring
Product Specification	ASTM F3261-17 Class I, Type B, Grade 1, Backing class B
Notice d'installation	Flottant 5G Dry
Limited Warranty (Public Environment)	15 ans
Limited Warranty (Domestic Environment)	Limited lifetime warranty
Level of use domestic (EN ISO 10874)	Class Heavy Residential
Level of use commercial (EN ISO 10874)	Class Heavy Commercial



Bjelin bjelin.com support@bjelin.com

Copyright 2024 Bjelin Sweden AB. Weights and dimensions may have minor variations depending on external circumstances. Bjelin reserves the right to deviate from the weight and dimensions in this technical data sheet. Technologies mentioned may be subject to patent protection and invented by Välinge Innovation AB (www.valinge.se/patents). Use of trademarks herein owned by Bjelin Sweden AB or Välinge Innovation AB is under license.



Pour consulter les instructions de pose, les consignes et autres informations sur le produit, scannez le code QR, ou rendez-vous sur [bjelin.fr](http://bjelin.fr).