

# Vinyl Planks

## DENALI SANIBEL

Sanibel je revidirani, vrlo voljeni švedski klasik u svijetlom tonu. Svijetao je i dodaje svježinu vašoj sobi. Topla nijansa nudi graciozan osjećaj koji nadopunjuje sve stilove uređenja.



### Specifikacija

| OPĆENITO               |                            |
|------------------------|----------------------------|
| Površinska obrada      | UV cured acrylic           |
| Uzorak                 | Podna daska                |
| Spoj                   | 5G Dry                     |
| Jezgra                 | SPC - Rigid polymeric core |
| Mikrobevel             | 4 sided micro bevel        |
| Boja                   | Warm white                 |
| DIMENZIJE              |                            |
| Širina                 | 228 mm                     |
| Dužina                 | 1830 mm                    |
| Visina                 | 6.5 mm                     |
| Debljina gornjeg sloja | 20 mil (0,55 mm)           |
| PAKET                  |                            |
| Količina u paketu      | 5                          |
| m² / paket             | 2,09 m²                    |
| m² po paleti           | 100,2 m²                   |
| Težina po m²           | 9,13 kg                    |
| Težina po paketu       | 19,7 kg                    |

| KLASIFIKACIJA I SIGURNOST                |                                                         |
|------------------------------------------|---------------------------------------------------------|
| Greenguard Gold                          | Greenguard Gold Certified                               |
| A+                                       | Yes                                                     |
| Dimensional stability (ISO 23999)        | Pass - max < 0.2%/linear ft (305 mm)                    |
| Curling (ISO 23999 )                     | Pass - <1 mm                                            |
| Effect of Castor Chair (ISO 4918)        | Pass - 25 000 rev                                       |
| Statički koeficijent trenja (ASTM D2047) | Suho: >0,6                                              |
| Kritični tok zračenja (ASTM E648)        | Klasa 1: ≥ 0,45 W/cm²                                   |
| Održivost - VOC                          | Greenguard Gold certificirano                           |
| Ftalati i teški metali                   | Ftalati i teški metali ispod granice detekcije          |
| Klasa prijenosa zvuka (ASTM F90)         | 54                                                      |
| Klasa izolacije od udara                 | 53                                                      |
| Smanjenje prijenosa zvuka (ASTM E2179)   | 20                                                      |
| RAZNO                                    |                                                         |
| Otpornost na vodu                        | Visoka                                                  |
| Construction                             | SPC - Rigid polymeric core - modular resilient flooring |
| Product Specification                    | ASTM F3261-17 Class I, Type B, Grade 1, Backing class B |
| Instalacijska metoda                     | Plivajući 5G Dry                                        |
| Ograničeno jamstvo (javno okruženje)     | 15 godine                                               |
| Limited Warranty (Domestic Environment)  | Limited lifetime warranty                               |
| Level of use domestic (EN ISO 10874)     | Class Heavy Residential                                 |
| Level of use commercial (EN ISO 10874)   | Class Heavy Commercial                                  |



**Bjelin**   [bjelin.com](https://bjelin.com)   [hr-sales@bjelin.com](mailto:hr-sales@bjelin.com)

Copyright 2026 Bjelin Sweden AB. Weights and dimensions may have minor variations depending on external circumstances. Bjelin reserves the right to deviate from the weight and dimensions in this technical data sheet. Technologies mentioned may be subject to patent protection and invented by Välinge Innovation AB ([www.valinge.se/patents](https://www.valinge.se/patents)). Use of trademarks herein owned by Bjelin Sweden AB or Välinge Innovation AB is under license.



*Za upute o postavljanju i održavanju te daljnje informacije o proizvodu skenirajte QR kod ili posjetite [bjelin.com](https://bjelin.com).*