

Rigid Core

PLANKS AUSTIN DRIFTWOOD



Colour
Driftwood



Pattern
Plank

Austinissa on sään kuluttaman ajopuun ulkonäkö, joka on saatu aikaan sekoittamalla luonnollisensävyistä hopeanharmaata ja kerman valkoista. Lattian kauniit, tasapainoiset väriaihtelut luovat syvän neutraalin pohjasävy, joka sulautuu täydellisesti sekä lämpimiin että kylmiin sisustuspaletteihin.



Specification

GENERAL

Surface finishing	UV cured acrylic
Colour	Driftwood
Pattern	Plank
Locking system	5G Dry
Core	SPC - Rigid polymeric core
Microbevel	4 sided micro bevel

DIMENSIONS

Width	228 mm
Length	1830 mm
Thickness	6.5 mm
Thickness of wear layer	20 mil (0,55 mm)

PACKAGE

Quantity in box	5
m² / box	2,09 m²
m² per pallet	100,2 m²
Weight per m²	9,13 kg
Weight per box	19,7 kg

CLASSIFICATION AND SAFETY

Greenguard Gold	Greenguard Gold Certified
A+	Yes
Dimensional stability (ISO 23999)	Pass - max < 0.2%/linear ft (305 mm)
Curling (ISO 23999)	Pass - <1 mm
Effect of Castor Chair (ISO 4918)	Pass - 25 000 rev
Static coefficient of friction (ASTM D2047)	Dry: >0.6
Critical Radiant flux (ASTM E648)	Class 1 : ≥ 0.45 W/cm²
Sustainability VOC	Greenguard Gold Certified
Phthalates & heavy metals	Phthalates and heavy metals below the detection limit
Sound transmission class (ASTM F90)	54
Impact insulation class	53
Sound transmission reduction (ASTM E2179)	20

MISC.

Water resistance	High
Construction	SPC - Rigid polymeric core - modular resilient flooring
Product Specification	ASTM F3261-17 Class I, Type B, Grade 1, Backing class B
Installation method	Floating 5G Dry
Limited warranty (public environment)	15 years
Limited Warranty (Domestic Environment)	Limited lifetime warranty
Level of use domestic (EN ISO 10874)	Class Heavy Residential
Level of use commercial (EN ISO 10874)	Class Heavy Commercial



Bjelin Finland Oy bjelin.com myynti@bjelin.com +358 40 9218055

Copyright 2025 Bjelin Sweden AB. Weights and dimensions may have minor variations depending on external circumstances. Bjelin reserves the right to deviate from the weight and dimensions in this technical data sheet. Technologies mentioned may be subject to patent protection and invented by Välinge Innovation AB (www.valinge.se/patents). Use of trademarks herein owned by Bjelin Sweden AB or Välinge Innovation AB is under license.



For installation and caring instructions, and further product information, scan the QR code or visit bjelin.com.