

Rigid Core

PLANKS AUSTIN DRIFTWOOD



Colour
Driftwood



Pattern
Plank

Austin har utformats för att framkalla den svala känslan av väderbiten svensk drivved, med en blandning av naturinspirerade silvergrå och krämvita nyanser. De vackra, balanserade färgvariationerna i golvet skapar en djup neutral ton som passar perfekt med både varma och kalla inredningspaletter.



Specification

GENERAL	
Surface finishing	UV cured acrylic
Colour	Driftwood
Pattern	Plank
Locking system	5G Dry
Core	SPC - Rigid polymeric core
Microbevel	4 sided micro bevel
DIMENSIONS	
Width	228 mm
Length	1830 mm
Thickness	6.5 mm
Thickness of wear layer	20 mil (0,55 mm)
PACKAGE	
Quantity in box	5
m ² / box	2,09 m ²
m ² per pallet	100,2 m ²
Weight per m ²	9,13 kg
Weight per box	19.7 kg

CLASSIFICATION AND SAFETY	
Greenguard Gold	Greenguard Gold Certified
A+	Yes
Dimensional stability (ISO 23999)	Pass - max < 0.2%/linear ft (305 mm)
Curling (ISO 23999)	Pass - <1 mm
Effect of Castor Chair (ISO 4918)	Pass - 25 000 rev
Static coefficient of friction (ASTM D2047)	Dry: >0.6
Critical Radiant flux (ASTM E648)	Class 1 : ≥ 0.45 W/cm ²
Sustainability VOC	Greenguard Gold Certified
Phthalates & heavy metals	Phthalates and heavy metals below the detection limit
Sound transmission class (ASTM F90)	54
Impact insulation class	53
Sound transmission reduction (ASTM E2179)	20
MISC.	
Water Resistance	High
Construction	SPC - Rigid polymeric core - modular resilient flooring
Product Specification	ASTM F3261-17 Class I, Type B, Grade 1, Backing class B
Installation method	Floating 5G Dry
Limited Warranty (Public Environment)	15 years
Limited Warranty (Domestic Environment)	Limited lifetime warranty
Level of use domestic (EN ISO 10874)	Class Heavy Residential
Level of use commercial (EN ISO 10874)	Class Heavy Commercial



Bjelin Sweden AB bjelin.com support@bjelin.se 020-51 50 10

Copyright 2025 Bjelin Sweden AB. Vikt och dimensioner kan ha mindre variationer beroende på yttre omständigheter. Bjelin förbehåller sig rätten att avvika från vikten och dimensionerna i detta tekniska datablad. Nämnade teknologier kan vara föremål för patentskydd och uppfunna av Välinge Innovation AB (www.valinge.se/patents). Användning av varumärken här ägda av Bjelin Sweden AB eller Välinge Innovation AB sker under licens.



For installation and caring instructions, and further product information, scan the QR code or visit bjelin.com.