

Rigid Core

PLANKS MILTON

WEATHERED GREY



Colour
Weathered grey



Pattern
Plank

Milton är ett klassiskt val som ger ett genuint utseende och en känsla av åldrat trä. Det är elegant och fängslande med en väderbiten touch. Den slående blandningen av naturliga nyanser och varma undertoner innebär att det smickrar alla färger i ditt hem, vilket gör det både praktisk och sofistikerat.



Specification

GENERAL

Surface finishing	UV cured acrylic
Colour	Weathered grey
Pattern	Plank
Locking system	5G Dry
Core	SPC - Rigid polymeric core
Microbevel	4 sided micro bevel

DIMENSIONS

Width	228 mm
Length	1830 mm
Thickness	6.5 mm
Thickness of wear layer	20 mil (0,55 mm)

PACKAGE

Quantity in box	5
m ² / box	2,09 m ²
m ² per pallet	100,2 m ²
Weight per m ²	9,13 kg
Weight per box	19.7 kg

CLASSIFICATION AND SAFETY

Greenguard Gold	Greenguard Gold Certified
A+	Yes
Dimensional stability (ISO 23999)	Pass - max < 0.2%/linear ft (305 mm)
Curling (ISO 23999)	Pass - <1 mm
Effect of Castor Chair (ISO 4918)	Pass - 25 000 rev
Static coefficient of friction (ASTM D2047)	Dry: >0.6
Critical Radiant flux (ASTM E648)	Class 1 : ≥ 0.45 W/cm ²
Sustainability VOC	Greenguard Gold Certified
Phthalates & heavy metals	Phthalates and heavy metals below the detection limit
Sound transmission class (ASTM F90)	54
Impact insulation class	53
Sound transmission reduction (ASTM E2179)	20

MISC.

Water Resistance	High
Construction	SPC - Rigid polymeric core - modular resilient flooring
Product Specification	ASTM F3261-17 Class I, Type B, Grade 1, Backing class B
Installation method	Floating 5G Dry
Limited Warranty (Public Environment)	15 years
Limited Warranty (Domestic Environment)	Limited lifetime warranty
Level of use domestic (EN ISO 10874)	Class Heavy Residential
Level of use commercial (EN ISO 10874)	Class Heavy Commercial



Bjelin Sweden AB bjelin.com support@bjelin.se 020-51 50 10

Copyright 2025 Bjelin Sweden AB. Vikt och dimensioner kan ha mindre variationer beroende på yttre omständigheter. Bjelin förbehåller sig rätten att avvika från vikten och dimensionerna i detta tekniska datablad. Nämnade teknologier kan vara föremål för patentskydd och uppfunna av Välinge Innovation AB (www.valinge.se/patents). Användning av varumärken här ägda av Bjelin Sweden AB eller Välinge Innovation AB sker under licens.



For installation and caring instructions, and further product information, scan the QR code or visit bjelin.com.