

Rigid Core

PLANKS CANTON SMOKED GREY



Pattern
Plank

Smoked Grey creates a contrast between dark and light, bringing out a soft smoked shade in the floor, beautifully enriching the depth of the colour variations. It's a sophisticated and natural-looking Swedish floor that's the perfect backdrop for either subtle or strong colours.



Specification

GENERAL	
Surface finishing	UV cured acrylic
Colour	Smoked grey
Pattern	Plank
Locking system	5G Dry
Core	SPC - Rigid polymeric core
Microbevel	4 sided micro bevel
DIMENSIONS	
Width	228 mm
Width (ISO 24337)	9"
Length	1830 mm
Length (ISO 24337)	72"
Thickness	6.5 mm
Thickness (ASTM F387)	1/4"
Thickness of wear layer	0.55 mm
Thickness of wear layer (ASTM F410)	20 mil (0.02")
PACKAGE	
Quantity in box	5
m² / box	2.09 m²
sq.ft per box	22.47 sq.ft
m² per pallet	100.2 m²
sq.ft per pallet	1078.4 sq.ft
Weight per m²	9.13 kg
Weight per sq.ft	1.87 lbs
Weight per box	19.7 kg
Weight per box	43.33 lbs

CLASSIFICATION AND SAFETY	
Greenguard Gold	Greenguard Gold Certified
A+	Yes
Dimensional stability (ISO 23999)	Pass - max < 0.2%/linear ft (305 mm)
Curling (ISO 23999)	Pass - <1 mm
Effect of Castor Chair (ISO 4918)	Pass - 25 000 rev
Residual indentation (ASTM F1914)	Pass - <0.18 mm(34 kg, 6.35 mm flat foot)
Static load (ASTM F970)	Pass - <0.13 mm indent, 250 lb/N2
Surface integrity (ASTM F1914)	No puncture through wear layer/decor into core
Resistance to chemicals (ASTM F925)	Pass
Resistance to heat (ASTM F1514)	Pass
Resistance to light (ASTM F1515)	Pass
Static coefficient of friction (ASTM D2047)	Dry: >0.6
Critical Radiant flux (ASTM E648)	Class 1 : ≥ 0.45 W/cm²
Sustainability VOC	Greenguard Gold Certified
Phthalates & heavy metals	Pthalates and heavy metals below the detection limit
Sound transmission class (ASTM F90)	54
Impact insulation class	53
Sound transmission reduction (ASTM E2179)	20
MISC.	
Water Resistance	High
Construction	SPC - Rigid polymeric core - modular resilient flooring
Product Specification	ASTM F3261-17 Class I, Type B, Grade 1, Backing class B
Installation method	Floating 5G Dry
Limited Warranty (Public Environment)	15 years
Limited Warranty (Domestic Environment)	Limited lifetime warranty
Level of use domestic (EN ISO 10874)	Class Heavy Residential
Level of use commercial (EN ISO 10874)	Class Heavy Commercial



Bjelin Sweden AB bjelin.com support@bjelin.se +46-771-101099

Copyright 2024 Bjelin Sweden AB. Weights and dimensions may have minor variations depending on external circumstances. Bjelin reserves the right to deviate from the weight and dimensions in this technical data sheet. Technologies mentioned may be subject to patent protection and invented by Välinge Innovation AB (www.valinge.se/patents). Use of trademarks herein owned by Bjelin Sweden AB or Välinge Innovation AB is under license.



For installation and caring instructions, and further product information, scan the QR code or visit bjelin.com.