

Vinyl Planks

DENALI NEWHAVEN



图案
直板板材

注重耐用性的传统或现代装饰。轻柔本色色系具有迷人的聪慧感和传统感。



规格

基础信息	
地板品类	Vinyl Flooring
表面处理	紫外光固化丙烯酸
颜色	自然本色系
颜色选择	Light natural
图案	直板板材
锁扣系统	5G Dry
芯材	SPC - 刚性聚合物芯材
微倒角	4 sided micro bevel
尺寸	
宽	228 mm
长	1830 mm
高	6.5 mm
磨损层的厚度	20 mil (0,55 mm)
包装	
盒内数量	5
平方米/箱	2,09 平方米
平方米/托盘	100,2 平方米
每平方米重量	9,13 kg
每盒重量	19,7 kg

分类和安全属性	
Greenguard Gold	Greenguard Gold 认证
A+	Yes
尺寸稳定性 (ISO 23999)	Pass - max < 0.2%/linear ft (305 mm)
Curling (ISO 23999)	通过测试 - < 1mm
脚轮座椅的测试 (ISO 4918)	通过测试 - 25000 转
静摩擦系数 (ASTM D2047)	干: >0.6
临界辐射通量 (ASTM E648)	1级: ≥ 0.45 W/cm²
可持续性 VOC	Greenguard Gold 认证
邻苯二甲酸盐和重金属	邻苯二甲酸盐和重金属低于检测限
声音传输等级 (ASTM F90)	54
耐冲击等级	53
减少声音传播 (ASTM E2179)	20
其他	
产品集	Denali
防水性	高
结构	SPC - 刚性聚合物芯材 - 模块化弹性地板
产品规格	ASTM F3261-17 Class I, Type B, Grade 1, Backing class B
安装方式	悬浮式 5G Dry
有限质保 (商业环境)	15 年
有限质保 (家庭使用环境)	有限终身保修
家用等级 (EN ISO 10874)	重型住宅类别
Level of use commercial (EN ISO 10874)	商用等级 (EN ISO 10874)



Bjelin bjelin.com support@bjelin.com +86 21 522 822 62

Copyright 2026 Bjelin Sweden AB. Weights and dimensions may have minor variations depending on external circumstances. Bjelin reserves the right to deviate from the weight and dimensions in this technical data sheet. Technologies mentioned may be subject to patent protection and invented by Välinge Innovation AB (www.valinge.se/patents). Use of trademarks herein owned by Bjelin Sweden AB or Välinge Innovation AB is under license.



有关安装和护理说明以及进一步的产品信息，请扫描QR码，或访问bjelin.com。