

Rigid Core

PLANKS NEWHAVEN



Colour
Light natural



Mønster
Plank

Newhaven er et skandinavisk-inspirert tidløst valg som gir hjemmet ditt et varig utseende – bruk det i generasjoner fremover. Med en lysere tone enn tradisjonelle eikegulv og med den utsøkte følelsen av nysaget tømmer, får den frem en ekte følelse av natur.



Spesifikasjon

GENERELT

Overflatebehandling	UV cured acrylic
Colour	Light natural
Mønster	Plank
Fug	5G Dry
Kjerne	SPC - Rigid polymeric core
Mikrobevel	4 sided micro bevel

MÅL

Bredde	228 mm
Lengde	1830 mm
Høyde	6.5 mm
Slitesjiktets tykkelse	20 mil (0,55 mm)

EMBALLASJE

Antall i pakken	5
m ² i pakken	2,09 m ²
m ² per pall	100,2 m ²
Vekt pr. m ²	9,13 kg
Vekt pr. pakke	19,7 kg

KLASSIFISERING OG SIKKERHET

Greenguard Gold	Greenguard Gold Certified
A+	Yes
Dimensional stability (ISO 23999)	Pass - max < 0.2%/linear ft (305 mm)
Curling (ISO 23999)	Pass - <1 mm
Effect of Castor Chair (ISO 4918)	Pass - 25 000 rev
Statisk friksjonskoeffisient (ASTM D2047)	Tørt > 0,6
Kritisk strålefluks (ASTM E648)	Klasse 1: ≥ 0,45 W/cm ²
Bærekraft VOC	Greenguard Gold Certified
Ftalater & tungmetaller	Ftalater og tungmetaller under påvisbar grense
Lyddempingsklasse (ASTM F90)	54
Støtisoleringsklasse	53
Lyddemping (ASTM E2179)	20

ANNEN

Water Resistance	High
Construction	SPC - Rigid polymeric core - modular resilient flooring
Product Specification	ASTM F3261-17 Class I, Type B, Grade 1, Backing class B
Leggemetode	Flytende 5G Tørt
Limited Warranty (Public Environment)	15 år
Limited Warranty (Domestic Environment)	Limited lifetime warranty
Level of use domestic (EN ISO 10874)	Class Heavy Residential
Level of use commercial (EN ISO 10874)	Class Heavy Commercial
NOBB-nummer	60145766



Bjelin bjelin.com support@bjelin.com +47 3322 2300

Copyright 2025 Bjelin Sweden AB. Weights and dimensions may have minor variations depending on external circumstances. Bjelin reserves the right to deviate from the weight and dimensions in this technical data sheet. Technologies mentioned may be subject to patent protection and invented by Välinge Innovation AB (www.valinge.se/patents). Use of trademarks herein owned by Bjelin Sweden AB or Välinge Innovation AB is under license.



Skann QR-koden med mobilen eller besøk bjelin.com for å se informasjon om legging og ytterligere produktinformasjon.