

# Rigid Core

## BJELIN SONOMA MEDIUM SMOKED



Colour  
Medium smoked



Pattern  
Plank

Sonoma on eloisa sekoitus lämpimiä sävyjä – se tuo mieleen paahdetut kastanjat. Se on suunniteltu upeaksi sisustuksen perustaksi kotiisi, ja sen syvät ja rikkaat sävyt luovat upean ja karismaattisen aitouden tunteen.



### Specification

#### GENERAL

|                   |                            |
|-------------------|----------------------------|
| Surface finishing | UV cured acrylic           |
| Colour            | Medium smoked              |
| Pattern           | Plank                      |
| Locking system    | 5G Dry                     |
| Core              | SPC - Rigid polymeric core |
| Microbevel        | 4 sided micro bevel        |

#### DIMENSIONS

|                         |                  |
|-------------------------|------------------|
| Width                   | 228 mm           |
| Length                  | 1830 mm          |
| Thickness               | 6.5 mm           |
| Thickness of wear layer | 20 mil (0,55 mm) |

#### PACKAGE

|                           |                      |
|---------------------------|----------------------|
| Quantity in box           | 5                    |
| m <sup>2</sup> / box      | 2,09 m <sup>2</sup>  |
| m <sup>2</sup> per pallet | 100,2 m <sup>2</sup> |
| Weight per m <sup>2</sup> | 9,13 kg              |
| Weight per box            | 19.7 kg              |

#### CLASSIFICATION AND SAFETY

|                                             |                                                       |
|---------------------------------------------|-------------------------------------------------------|
| Greenguard Gold                             | Greenguard Gold Certified                             |
| A+                                          | Yes                                                   |
| Dimensional stability (ISO 23999)           | Pass - max < 0.2%/linear ft (305 mm)                  |
| Curling (ISO 23999 )                        | Pass - <1 mm                                          |
| Effect of Castor Chair (ISO 4918)           | Pass - 25 000 rev                                     |
| Static coefficient of friction (ASTM D2047) | Dry: >0.6                                             |
| Critical Radiant flux (ASTM E648)           | Class 1 : ≥ 0.45 W/cm <sup>2</sup>                    |
| Sustainability VOC                          | Greenguard Gold Certified                             |
| Phthalates & heavy metals                   | Phthalates and heavy metals below the detection limit |
| Sound transmission class (ASTM F90)         | 54                                                    |
| Impact insulation class                     | 53                                                    |
| Sound transmission reduction (ASTM E2179)   | 20                                                    |

#### MISC.

|                                         |                                                         |
|-----------------------------------------|---------------------------------------------------------|
| Water resistance                        | High                                                    |
| Construction                            | SPC - Rigid polymeric core - modular resilient flooring |
| Product Specification                   | ASTM F3261-17 Class I, Type B, Grade 1, Backing class B |
| Installation method                     | Floating 5G Dry                                         |
| Limited warranty (public environment)   | 15 years                                                |
| Limited Warranty (Domestic Environment) | Limited lifetime warranty                               |
| Level of use domestic (EN ISO 10874)    | Class Heavy Residential                                 |
| Level of use commercial (EN ISO 10874)  | Class Heavy Commercial                                  |



**Bjelin Finland Oy**   [bjelin.com](https://bjelin.com)   [myynti@bjelin.com](mailto:myynti@bjelin.com)   +358 40 9218055

Copyright 2025 Bjelin Sweden AB. Weights and dimensions may have minor variations depending on external circumstances. Bjelin reserves the right to deviate from the weight and dimensions in this technical data sheet. Technologies mentioned may be subject to patent protection and invented by Välinge Innovation AB ([www.valinge.se/patents](https://www.valinge.se/patents)). Use of trademarks herein owned by Bjelin Sweden AB or Välinge Innovation AB is under license.



For installation and caring instructions, and further product information, scan the QR code or visit [bjelin.com](https://bjelin.com).