

Vinyl Planks

DENALI TACOMA

Tacoma ima bogate tonove tamno smeđe i dodaje dramatičan i sofisticiran dodir vašem podu. Topao je i privlačan, poput bujne švedske šume, i može se upariti s bezvremenskim neutralnim ili bogatim, raskošnim tonovima.



Specifikacija

OPĆENITO

Površinska obrada	UV cured acrylic
Uzorak	Podna daska
Spoj	5G Dry
Jezgra	SPC - Rigid polymeric core
Mikrobevel	4 sided micro bevel
Boja	Hard smoked

DIMENZIJE

Širina	228 mm
Dužina	1830 mm
Visina	6.5 mm
Debljina gornjeg sloja	20 mil (0,55 mm)

PAKET

Količina u paketu	5
m ² / paket	2,09 m ²
m ² po paleti	100,2 m ²
Težina po m ²	9,13 kg
Težina po paketu	19,7 kg

KLASIFIKACIJA I SIGURNOST

Greenguard Gold	Greenguard Gold Certified
A+	Yes
Dimensional stability (ISO 23999)	Pass - max < 0.2%/linear ft (305 mm)
Curling (ISO 23999)	Pass - <1 mm
Effect of Castor Chair (ISO 4918)	Pass - 25 000 rev
Statički koeficijent trenja (ASTM D2047)	Suho: >0,6
Kritični tok zračenja (ASTM E648)	Klasa 1: ≥ 0,45 W/cm ²
Održivost - VOC	Greenguard Gold certificirano
Ftalati i teški metali	Ftalati i teški metali ispod granice detekcije
Klasa prijenosa zvuka (ASTM F90)	54
Klasa izolacije od udara	53
Smanjenje prijenosa zvuka (ASTM E2179)	20

RAZNO

Otpornost na vodu	Visoka
Construction	SPC - Rigid polymeric core - modular resilient flooring
Product Specification	ASTM F3261-17 Class I, Type B, Grade 1, Backing class B
Instalacijska metoda	Plivajući 5G Dry
Ograničeno jamstvo (javno okruženje)	15 godine
Limited Warranty (Domestic Environment)	Limited lifetime warranty
Level of use domestic (EN ISO 10874)	Class Heavy Residential
Level of use commercial (EN ISO 10874)	Class Heavy Commercial



Bjelin bjelin.com hr-sales@bjelin.com

Copyright 2026 Bjelin Sweden AB. Weights and dimensions may have minor variations depending on external circumstances. Bjelin reserves the right to deviate from the weight and dimensions in this technical data sheet. Technologies mentioned may be subject to patent protection and invented by Välinge Innovation AB (www.valinge.se/patents). Use of trademarks herein owned by Bjelin Sweden AB or Välinge Innovation AB is under license.



Za upute o postavljanju i održavanju te daljnje informacije o proizvodu skenirajte QR kod ili posjetite bjelin.com.