

Vinyl Planks

ACADIA COLFAX



Pattern
Plank

Kempton in the shade Meadow pairs beautifully with warm neutrals, natural materials and both classic and contemporary interiors. It's an excellent choice if you want your space to have a grounded and sophisticated feel.



Specification

GENERAL

Type of floor	Vinyl Flooring
Surface finishing	UV cured acrylic
Colour	Natural
Staining	Willow
Pattern	Plank
Locking system	5G
Core	SPC - Rigid polymeric core
Microbevel	4 sided micro bevel
Residual indentation (EN ISO 24343-1)	≤0.02 mm (norm ≤0.10 mm)
Resistance to large ball (EN ISO 24343-1)	1800 mm (norm 1600 mm)
Antistatic and electrical properties (EN 14041 (EN 1815))	<2kV
Light fastness (EN ISO 105-B02)	≥6
Supports underfloor heating (EN 12524)	yes (max 27°C)
IS - Impact sound improvement (integrated acoustic underlay) (EN ISO 717-2)	ΔLw = 21 dB
Substances of Very High Concern (EN 717-1)	SVHC free

DIMENSIONS

Width	229 mm
Width (ISO 24337)	9"
Length	1200 mm
Length (ISO 24337)	47"
Thickness	5.3 mm
Thickness (ASTM F387)	2"
Thickness of wear layer	20 mil (0,55 mm)
Thickness of wear layer (ASTM F410)	0.02"

PACKAGE

Quantity in box	8
m ² / box	2.235 m ²
sq.ft per box	24.06 sqft
m ² per pallet	93.87 m ²
sq.ft per pallet	1010.4 sqft
Weight per m ²	8.74 kg
Weight per sq.ft	19.27 lbs
Weight per box	18.63 kg
Weight per box	41.07 lbs

CLASSIFICATION AND SAFETY

A+	Yes
Fire Resistance (EN 13501)	Bfl-s1
Dimensional stability (ISO 23999)	≤0.05% (norm ≤0.25%)
Wear resistance (EN 14354)	≥7000 (norm ≥2000)
Effect of Castor Chair (ISO 4918)	Pass - 25 000 rev
Slip resistance (EN 13893 / DIN 51130)	DS/R9
Resistance to stain and chemicals (EN ISO 26987)	INDEX 0 (very good)
Thermal resistance (EN 12667)	0.042 m ² k/W
Formaldehyde emission (EN 717-1)	Class E1
Sustainability VOC	A+

MISC.

Locking strength	long edge 4.5 kN/m, short edge 5.5 kN/m
Limited warranty (public environment)	15 years
Limited Warranty (Domestic Environment)	Limited lifetime warranty
Level of use domestic (EN ISO 10874)	Class Heavy Residential
Level of use commercial (EN ISO 10874)	Class Heavy Commercial



Bjelin bjelin.com support@bjelin.com +46-771-101099

Copyright 2026 Bjelin Sweden AB. Weights and dimensions may have minor variations depending on external circumstances. Bjelin reserves the right to deviate from the weight and dimensions in this technical data sheet. Technologies mentioned may be subject to patent protection and invented by Välinge Innovation AB (www.valinge.se/patents). Use of trademarks herein owned by Bjelin Sweden AB or Välinge Innovation AB is under license.



For installation and caring instructions, and further product information, scan the QR code or visit bjelin.com.