

Woodura Planks 3.0

SKIVARP 3.0 XL



Type of wood
Oak



Grading
Nature



Surface finishing
Pro matt lacquer



Water resistance
High

Skivarp is a stunning grey, matt-lacquered hardened wood floor that's both sophisticated and stylish. The Mineral Grey shade has been paired with the Nature grading, providing a natural colour variation. Made from FSC-certified European oak, this class 33 product is extremely durable and ideal for heavy-traffic spaces like hotels, shops, offices and cafés – or the entrance of your home. The matt lacquered finish makes the floor easy to maintain while protecting it from stains.



Specification

GENERAL

Type of floor	Hardened wood
Type of wood	Oak
Grading	Nature
Surface finishing	Pro matt lacquer
Staining	Mineral Grey
Light/dark	Medium dark
Pattern	Plank
Locking system	Välinge 5G Dry®
Core	HDF

DIMENSIONS

Format	XL
Width	206 mm
Length	2200 mm
Thickness	11,3 mm
Thickness of wear layer	0,6 mm

PACKAGE

Quantity in box	4 pcs
m ² / box	1,81 m²
m ² per pallet	87 m²
Weight per m ²	11 kg
Weight per box	20 kg

CLASSIFICATION AND SAFETY

Supports Underfloor Heating	Yes
Water resistance	High
Fire Resistance (EN 13501)	Cfl-s1
Thermal conductivity (EN 12664)	0,16 W/(m*K)
Thermal resistance (EN 12667)	0.07 m²K/W
Formaldehyde emission (EN 717-1)	E1 <=0.1 ppm (typical value <= 0.05 ppm)
Brinell hardness (EN 1534)	10 HB (average value)
Impact resistance (EN 14354)	EC3
Thickness swelling (EN 14354)	<10% (5% typical)
Wear resistance (EN 14354)	> 6000 cycles
Slip resistance (USRV) (CEN//TS 15676)	40
FSC	FSC Mix (FSC-C140725)
SundaHus	Evaluated by SundaHus
CE Marked	Yes
Limited warranty (public environment)	10 years
Limited warranty (home environment)	Limited Lifetime Warranty
Level of use domestic (EN ISO 10874)	Class heavy Residential (Class 23)
Level of use commercial (EN ISO 10874)	Class heavy commercial (Class 33)



woodura®

Bjelin bjelin.com support@bjelin.com

Copyright 2026 Bjelin Sweden AB. Weights and dimensions may have minor variations depending on external circumstances. Bjelin reserves the right to deviate from the weight and dimensions in this technical data sheet. Technologies mentioned may be subject to patent protection and invented by Välinge Innovation AB (www.valinge.se/patents). Use of trademarks herein owned by Bjelin Sweden AB or Välinge Innovation AB is under license.



For installation and caring instructions, and further product information, scan the QR code or visit bjelin.com.