

Woodura Planks 3.0

LYA 3.0 XXL

Vrsta drveta
HrastKlase
SelectPovršinska obrada
Četkani mat lakBoja
NaturalUzorak
Podna daskaOtpornost na vodu
Visoka

LYA je klasičan skandinavski brušeni i lakirani učvršćeni drveni pod. Bezvremenska nijansa Natural uparena je sa skladnom klasom Select uredna izgleda. Brušena i lakirana površina izrađena je od europskog hrasta s certifikatom Vijeća za nadzor šuma (FSC). Površina vam nudi prirodnu drvenu teksturu sličnu teksturi nauljenih podova, no ovi su podovi jednostavniji za čišćenje i održavanje zahvaljujući laku. Postavljanje brušenih i lakiranih površina preporučujemo u svim prostorima u domu.



Specifikacija

OPĆENITO

Vrsta podne obloge	Učvršćeno drvo
Vrsta drveta	Hrast
Klase	Select
Površinska obrada	Četkani mat lak
Boja	Natural
Svijetlo/tamno	Srednje tamno
Uzorak	Podna daska
Spoj	Välinge 5G® Dry™
Jezgra	HDF
Mikrobevel	4 sided

DIMENZIJE

Format	XXL
Širina	271 mm
Dužina	2378 mm
Visina	11 mm
Debljina gornjeg sloja	0,6 mm

PAKET

Količina u paketu	3 kom
m ² / paket	1,93
m ² po paleti	93 m ²
Težina po m ²	11 kg
Težina po paketu	22 kg

KLASIFIKACIJA I SIGURNOST

Podržava podno grijanje	Da
Otpornost na vodu	Visoka
Otpornost na vatru (EN 13501)	Cfl-s1
Toplinska vodljivost (EN 12664)	0,16 W/(m*K)
Toplinska otpornost (EN 12667)	0,07 m ² K/W
Emisija formaldehida (EN 717-1)	E1<=0,124 mg/m3
Ocjena tvrdoće (EN 1534)	8 HB (average value)
Otpornost na udarce (EN 14354)	EC3
Debljina oticanja (EN 14354)	<10% (5% tipično)
Otpornost na habanje (EN 14354)	> 1000 ciklusa
FSC	FSC Mix (DNV-COC-001624)
SundaHus	Certificirano od strane SundaHus
Svanen	Da (3029 0021)
Greenguard Gold	Greenguard Gold Certified
CE označeno	Da
Ograničeno jamstvo (javno okruženje)	30 godine
Ograničeno jamstvo (kućno okruženje)	30 godine
Razina kućne upotrebe (EN ISO 10874)	Razina upotrebe u kućanstvu. Klasa teške stambene (klasa 22)



woodura®

Bjelin Croatia d.o.o | bjelin.com | hr-sales@bjelin.com

Copyright 2024 Bjelin Sweden AB. Weights and dimensions may have minor variations depending on external circumstances. Bjelin reserves the right to deviate from the weight and dimensions in this technical data sheet. Technologies mentioned may be subject to patent protection and invented by Välinge Innovation AB (www.valinge.se/patents). Use of trademarks herein owned by Bjelin Sweden AB or Välinge Innovation AB is under license.



Za upute o postavljanju i održavanju te daljnje informacije o proizvodu skenirajte QR kod ili posjetite bjelin.com.