


Woodura Planks 3.0

LARVIK XXL POWDER WHITE 3.0



Larvik is a contemporary hardened wood floor. The brilliant Powder White shade has been paired with the Select grading, which is clean-looking and harmonious. Made from FSC-certified European oak, the brushed finish provides a natural wood feel – similar to oiled floors – but the finish makes the floors easier to clean and maintain. We recommend a brushed finish in all areas of the home.



Specification

GENERAL

Type of floor	Hardened wood
Type of wood	Oak
Grading	Select
Surface finishing	Brushed finish
Staining	Powder White
Light/dark	Light
Pattern	Plank
Locking system	Välinge 5G® Dry™
Core	HDF
Microbevel	4 sided
Level of use	Residential

DIMENSIONS

Format	XXL
Width (ISO 24337)	10.7"
Length (ISO 24337)	93.6
Thickness (ASTM F387)	0.43"
Thickness of wear layer (ASTM F410)	.02"
Weight per m ²	24 lbs

PACKAGE

Quantity in box	3 pcs
sq.ft per box	20.81 sqft
sq.ft per pallet	999 sqft
Weight per box	47.8 lbs

CLASSIFICATION AND SAFETY

Supports Underfloor Heating	Yes
Water resistance	High
Fire Resistance (EN 13501)	Cfl-s1
Thermal conductivity (EN 12664)	0.16 W/(m*K)
Thermal resistance (EN 12667)	0.07 m²K/W
Formaldehyde emission (EN 717-1)	E1<=0.124 mg/m3
Brinell hardness (EN 1534)	8 HB (average value)
Impact resistance (EN 14354)	EC3
Thickness swelling (EN 14354)	<10% (5% typical)
Wear resistance (EN 14354)	> 1000 cycles
FSC	FSC Mix (DNV-COC-001624)
SundaHus	Evaluated by SundaHus
Svanen	Yes (3029 0021)
Greenguard Gold	Greenguard Gold Certified
CE Marked	Yes
Warranty (commercial)	10 years
Warranty (residential)	Limited Lifetime Warranty
Level of use domestic (EN ISO 10874)	Class Moderate residential (Class 22)
MISC.	
NOBB-nummer	60085983



woodura®

Bjelin bjelin.com us-support@bjelin.com

Copyright 2025 Bjelin Sweden AB. Weights and dimensions may have minor variations depending on external circumstances. Bjelin reserves the right to deviate from the weight and dimensions in this technical data sheet. Technologies mentioned may be subject to patent protection and invented by Välinge Innovation AB (www.valinge.se/patents). Use of trademarks herein owned by Bjelin Sweden AB or Välinge Innovation AB is under license.



For installation and caring instructions, and further product information, scan the QR code or visit bjelin.com.