


# Woodura Planks 3.0

## VISTORP 3.0 L



Vistorp er et pudderhvitt, mattlakkert herdet tregulv i ekte svensk stil. Powder White er en nyanse som gjør rommet lysere, og Select-sorteringen understreker det rene og harmoniske utseendet. Dette er et produkt i klasse 33 produsert av FSC-sertifisert eik. Det er ekstremt slitesterkt og ideelt for trafikkerte områder som hoteller, butikker, kontorlokaler og kafeer – eller gangen hjemme hos deg selv. Den mattlakkerte overflaten gjør gulvet enkelt å vedlikeholde og beskytter mot flekker.



### Spesifikasjon

#### GENERELT

Type gulv	<b>Herdet tregulv</b>
Treslag	<b>Eik</b>
Sortering	<b>Select</b>
Overflatebehandling	<b>Pro matt lacquer</b>
Innfarging	<b>Powder White</b>
Lyst/mørkt	<b>Lyst</b>
Mønster	<b>Plank</b>
Fug	<b>Vålinge 5G® Dry™</b>
Kjerne	<b>HDF</b>

#### MÅL

Format	<b>L</b>
Bredde	<b>180 mm</b>
Lengde	<b>2000 mm</b>
Høyde	<b>9 mm</b>
Slitesjiktets tykkelse	<b>0,6 mm</b>

#### EMBALLASJE

Antall i pakken	<b>7</b>
m <sup>2</sup> i pakken	<b>2,5 m<sup>2</sup></b>
m <sup>2</sup> per pall	<b>90,7 m<sup>2</sup></b>
Vekt pr. m2	<b>9 kg</b>
Vekt pr. pakke	<b>22,7 kg</b>

#### KLASSIFISERING OG SIKKERHET

Egnet for gulvvarme	<b>Ja</b>
Vannbestandighet	<b>Høy</b>
Motstandsdyktighet mot brann (EN 13501)	<b>Cfl-s1</b>
Termisk ledningsevne (EN 12664)	<b>0,12 W/(m*K)</b>
Termisk motstand (EN 12667)	<b>0,075 (m2 x K)/W</b>
Formaldehyd emisjon (EN 717-1)	<b>E1 &lt;= 0,1 ppm (type verdi &lt;= 0,05 ppm)</b>
Brinellhardhet (EN 1534)	<b>8 HB (average value)</b>
Slagfasthet (EN 14354)	<b>EC3</b>
Svellingsgrad (EN 14354)	<b>&lt;10% (5% type verdi)</b>
Slitestykke (EN 14354)	<b>&gt; 6000 cycles</b>
Sklisikkerhet (USRV) (CEN//TS 15676)	<b>40</b>
FSC	<b>FSC Mix (FSC-C140725)</b>
SundaHus	<b>Bedømt av SundaHus</b>
Svanen	<b>Ja (3029 0021)</b>
Greenguard Gold	<b>Greenguard Gold Certified</b>
A+	<b>Yes</b>
M1	<b>Yes</b>
CE-merket	<b>Ja</b>
Garanti (offentlige miljø)	<b>30 år</b>
Garanti (private hjem)	<b>30 år</b>
Slitestykke i private hjem (EN ISO 10874)	<b>Moderat til sterkt trafikkerte områder (klasse 23)</b>
Slitestykke i offentlige miljø (EN ISO 10874)	<b>Høytrafikkområder (klasse 33)</b>

#### ANNEN

NOBB-nummer	<b>60085933</b>
-------------	-----------------



woodura®

**Bjelin** bjelin.com support@bjelin.com +47 3322 2300

Copyright 2025 Bjelin Sweden AB. Weights and dimensions may have minor variations depending on external circumstances. Bjelin reserves the right to deviate from the weight and dimensions in this technical data sheet. Technologies mentioned may be subject to patent protection and invented by Välinge Innovation AB (www.valinge.se/patents). Use of trademarks herein owned by Bjelin Sweden AB or Välinge Innovation AB is under license.



Skann QR-koden med mobilen eller besøk [bjelin.com](http://bjelin.com) for å se informasjon om legging og ytterligere produktinformasjon.