

Woodura Planks 3.0

YXENHULT 3.0 M



Type of wood
Oak



Grading
Blend



Surface finishing
Pro matt lacquer



Staining
Terra Brown



Pattern
Plank



Water resistance
High

El suelo de madera endurecida Yxenhult es un suelo con acabado laca mate que añade calidez y una sensación de lujo a un espacio. El profundo tono Terra Brown aporta carácter y la clasificación Blend, que incluye algunas variaciones de color, resalta las sutiles vetas. Fabricado con roble europeo con certificación FSC, este producto de clase 33 es extremadamente duradero e ideal para espacios de tránsito intenso, como hoteles, tiendas, oficinas y cafeterías, o la entrada de tu casa. El acabado laca mate facilita el mantenimiento del suelo y lo protege de las manchas.



Specification

GENERAL

Type of floor	Hardened wood
Type of wood	Oak
Grading	Blend
Surface finishing	Pro matt lacquer
Staining	Terra Brown
Light/dark	Medium dark
Pattern	Plank
Locking system	Välinge 5G® Dry™
Core	HDF

DIMENSIONS

Format	M
Width	151 mm
Length	2000 mm
Thickness	9 mm
Thickness of wear layer	0,6 mm

PACKAGE

Quantity in box	7
m² / box	2,1 m²
m² per pallet	95,13 m²
Weight per m²	9 kg
Weight per box	19,1 kg

CLASSIFICATION AND SAFETY

Supports Underfloor Heating	Yes
Water resistance	High
Fire Resistance (EN 13501)	Cfl-s1
Thermal conductivity (EN 12664)	0,12 W/(m*K)
Thermal resistance (EN 12667)	0,075 (m2 x K)/W
Formaldehyde emission (EN 717-1)	E1 <=0.1 ppm (typical value <= 0.05 ppm)
Brinell hardness (EN 1534)	8 HB (average value)
Impact resistance (EN 14354)	EC3
Thickness swelling (EN 14354)	<10% (5% typical)
Wear resistance (EN 14354)	> 6000 cycles
Slip resistance (USRV) (CEN//TS 15676)	40
FSC	FSC Mix (FSC-C140725)
SundaHus	Evaluated by SundaHus
A+	Yes
M1	Yes
CE Marked	Yes
Limited warranty (public environment)	10 years
Limited warranty (home environment)	Limited Lifetime Warranty
Level of use domestic (EN ISO 10874)	Class heavy Residential (Class 23)
Level of use commercial (EN ISO 10874)	Class heavy commercial (Class 33)



woodura®

Bjelin bjelin.com support@bjelin.com

Copyright 2025 Bjelin Sweden AB. Weights and dimensions may have minor variations depending on external circumstances. Bjelin reserves the right to deviate from the weight and dimensions in this technical data sheet. Technologies mentioned may be subject to patent protection and invented by Välinge Innovation AB (www.valinge.se/patents). Use of trademarks herein owned by Bjelin Sweden AB or Välinge Innovation AB is under license.



For installation and caring instructions, and further product information, scan the QR code or visit bjelin.com.