


Woodura Planks 3.0

VENESTAD 3.0 L



Venestad is a rich-looking, matt-lacquered hardened wood floor that brings the authentic feel of wood inside. Terra Brown is synonymous with nature, and the Select grading adds a clean and harmonious look. Made from FSC-certified European oak, this class 33 product is extremely durable and ideal for busy spaces like hotels, shops, offices and cafés – or a heavily trafficked area of your home. The matt lacquered finish makes the floor easy to maintain while protecting it from stains.



Specification

GENERAL

Type of floor	Hardened wood
Type of wood	Oak
Grading	Select
Surface finishing	Pro matt lacquer
Staining	Terra Brown
Light/dark	Dark
Pattern	Plank
Locking system	Välinge 5G® Dry™
Core	HDF

DIMENSIONS

Format	L
Width	180 mm
Width (ISO 24337)	7.09"
Length	2000 mm
Length (ISO 24337)	78.74"
Thickness	9 mm
Thickness (ASTM F387)	0.35"
Thickness of wear layer	0,6 mm
Thickness of wear layer (ASTM F410)	0.024"
Weight per m ²	19.9 lbs

PACKAGE

Quantity in box	7
m ² / box	2,5 m²
sq.ft per box	271 sqft
m ² per pallet	90,7 m²
sq.ft per pallet	976.5 sqft
Weight per m ²	9 kg
Weight per box	22,7 kg
Weight per box	50.1 lbs

CLASSIFICATION AND SAFETY

Supports Underfloor Heating	Yes
Water resistance	High
Fire Resistance (EN 13501)	Cfl-s1
Thermal conductivity (EN 12664)	0,12 W/(m*K)
Thermal resistance (EN 12667)	0,075 (m2 x K)/W
Formaldehyde emission (EN 717-1)	E1 <=0.1 ppm (typical value <= 0.05 ppm)
Brinell hardness (EN 1534)	8 HB (average value)
Impact resistance (EN 14354)	EC3
Thickness swelling (EN 14354)	<10% (5% typical)
Wear resistance (EN 14354)	> 6000 cycles
Slip resistance (USRV) (CEN//TS 15676)	40
FSC	FSC Mix
SundaHus	Evaluated by SundaHus
Svanen	Yes (3029 0021)
A+	Yes
M1	Yes
CE Marked	Yes
Limited warranty (public environment)	10 years
Limited warranty (home environment)	Limited Lifetime Warranty
Level of use domestic (EN ISO 10874)	Class heavy Residential (Class 23)
Level of use commercial (EN ISO 10874)	Class heavy commercial (Class 33)



Bjelin Sweden AB | bjelin.com | support@bjelin.se | +46-771-101099

Copyright 2024 Bjelin Sweden AB. Weights and dimensions may have minor variations depending on external circumstances. Bjelin reserves the right to deviate from the weight and dimensions in this technical data sheet. Technologies mentioned may be subject to patent protection and invented by Välinge Innovation AB (www.valinge.se/patents). Use of trademarks herein owned by Bjelin Sweden AB or Välinge Innovation AB is under license.



For installation and caring instructions, and further product information, scan the QR code or visit bjelin.com.