

Woodura Planks 3.0

## DALEN 3.0 M

Type of wood  
OakGrading  
BlendSurface finishing  
Pro Matte finishWater resistance  
High

Dalen is a bright hardened wood floor that's popular in Scandinavia. The clean-looking Powder White shade brings light, and the Blend grading includes some color variations, which adds character. Made from FSC-certified European oak, this class 33 product is extremely durable and ideal for heavy-traffic spaces like hotels, shops, offices and cafés – or the entrance of your home. The matt lacquered finish makes the floor easy to maintain while protecting it from stains.



## Specification

## GENERAL

|                   |                  |
|-------------------|------------------|
| Type of floor     | Hardened wood    |
| Type of wood      | Oak              |
| Grading           | Blend            |
| Surface finishing | Pro Matte finish |
| Staining          | Powder White     |
| Light/dark        | Light            |
| Pattern           | Plank            |
| Locking system    | Välinge 5G Dry®  |
| Core              | HDF              |
| Level of use      | Commercial       |

## DIMENSIONS

|                                     |            |
|-------------------------------------|------------|
| Format                              | M          |
| Width (ISO 24337)                   | 5.945"     |
| Length (ISO 24337)                  | 79.921"    |
| Thickness (ASTM F387)               | 0.362"     |
| Thickness of wear layer (ASTM F410) | 0.024"     |
| Weight per m²                       | 20.124 lbs |

## PACKAGE

|                  |               |
|------------------|---------------|
| Quantity in box  | 7             |
| sq.ft per box    | 23.132 sqft   |
| sq.ft per pallet | 1040.924 sqft |
| Weight per sq.ft | 1.870 lbs     |
| Weight per box   | 43.246 lbs    |

## CLASSIFICATION AND SAFETY

|                                        |                                          |
|----------------------------------------|------------------------------------------|
| Supports Underfloor Heating            | Yes                                      |
| Water resistance                       | High                                     |
| Fire Resistance (EN 13501)             | Cfl-s1                                   |
| Thermal conductivity (EN 12664)        | 0,12 W/(m*K)                             |
| Thermal resistance (EN 12667)          | 0,075 (m2 x K)/W                         |
| Formaldehyde emission (EN 717-1)       | E1 <=0.1 ppm (typical value <= 0.05 ppm) |
| Brinell hardness (EN 1534)             | 8 HB                                     |
| Impact resistance (EN 14354)           | EC3                                      |
| Thickness swelling (EN 14354)          | <10% (5% typical)                        |
| Wear resistance (EN 14354)             | > 6000 cycles                            |
| Slip resistance (USRV) (CEN//TS 15676) | 40                                       |
| FSC                                    | FSC Mix (FSC-C140725)                    |
| SundaHus                               | Evaluated by SundaHus                    |
| Svanen                                 | Yes (3029 0032)                          |
| A+                                     | Yes                                      |
| M1                                     | Yes                                      |
| CE Marked                              | Yes                                      |
| Warranty (commercial)                  | 10 years                                 |
| Warranty (residential)                 | Limited Lifetime Warranty                |
| Level of use domestic (EN ISO 10874)   | Class heavy Residential (Class 23)       |
| Level of use commercial (EN ISO 10874) | Class heavy commercial (Class 33)        |

## MISC.

|             |          |
|-------------|----------|
| NOBB-nummer | 60903326 |
| Revision nr | 1        |



woodura®

Bjelin bjelin.com us-support@bjelin.com

Copyright 2026 Bjelin Sweden AB. Weights and dimensions may have minor variations depending on external circumstances. Bjelin reserves the right to deviate from the weight and dimensions in this technical data sheet. Technologies mentioned may be subject to patent protection and invented by Välinge Innovation AB (www.valinge.se/patents). Use of trademarks herein owned by Bjelin Sweden AB or Välinge Innovation AB is under license.



For installation and caring instructions, and further product information, scan the QR code or visit [bjelin.com](http://bjelin.com).