

## Woodura Planks 3.0

### HASSLARP 3.0 L



Type of wood  
Oak



Grading  
Nature



Surface finishing  
Pro matt lacquer



Water resistance  
High

Hasslarp is a clean-looking, matt-lacquered hardened wood floor in a timeless Nordic style. The Misty White shade brings sophistication to a room, creating a sense of space, and the Nature grading provides depth to the floor design. Made from FSC-certified European oak, this class 33 product is extremely durable and ideal for busy spaces like hotels, shops, offices and cafés – or a heavily trafficked area of your home. The matt lacquered finish makes the floor easy to maintain while protecting it from stains.



## Specification

### GENERAL

Type of floor	<b>Hardened wood</b>
Type of wood	<b>Oak</b>
Grading	<b>Nature</b>
Surface finishing	<b>Pro matt lacquer</b>
Staining	<b>Misty White</b>
Light/dark	<b>Light</b>
Pattern	<b>Plank</b>
Locking system	<b>Välinge 5G Dry®</b>
Core	<b>HDF</b>

### DIMENSIONS

Format	<b>L</b>
Width	<b>180 mm</b>
Width (ISO 24337)	<b>7.087"</b>
Length	<b>2030 mm</b>
Length (ISO 24337)	<b>79.921"</b>
Thickness	<b>9,2 mm</b>
Thickness (ASTM F387)	<b>0.362"</b>
Thickness of wear layer	<b>0,6 mm</b>
Thickness of wear layer (ASTM F410)	<b>0.024"</b>
Weight per m <sup>2</sup>	<b>19.709 lbs</b>

### PACKAGE

Quantity in box	<b>7</b>
m <sup>2</sup> / box	<b>2,562 m<sup>2</sup></b>
sq.ft per box	<b>27.577 sqft</b>
m <sup>2</sup> per pallet	<b>92,232 m<sup>2</sup></b>
sq.ft per pallet	<b>992.777 sqft</b>
Weight per m <sup>2</sup>	<b>8,940 kg</b>
Weight per box	<b>23,06 kg</b>
Weight per box	<b>50.839 lbs</b>

### CLASSIFICATION AND SAFETY

Supports Underfloor Heating	<b>Yes</b>
Water resistance	<b>High</b>
Fire Resistance (EN 13501)	<b>Cfl-s1</b>
Thermal conductivity (EN 12664)	<b>0,12 W/(m*K)</b>
Thermal resistance (EN 12667)	<b>0,075 (m2 x K)/W</b>
Formaldehyde emission (EN 717-1)	<b>E1 &lt;=0.1 ppm (typical value &lt;= 0.05 ppm)</b>
Brinell hardness (EN 1534)	<b>8 HB (average value)</b>
Impact resistance (EN 14354)	<b>EC3</b>
Thickness swelling (EN 14354)	<b>&lt;10% (5% typical)</b>
Wear resistance (EN 14354)	<b>&gt; 6000 cycles</b>
Slip resistance (USRV) (CEN//TS 15676)	<b>40</b>
FSC	<b>FSC Mix (FSC-C140725)</b>
SundaHus	<b>Evaluated by SundaHus</b>
Greenguard Gold	<b>Greenguard Gold Certified</b>
A+	<b>Yes</b>
M1	<b>Yes</b>
CE Marked	<b>Yes</b>
Limited warranty (public environment)	<b>10 years</b>
Limited warranty (home environment)	<b>Limited Lifetime Warranty</b>
Level of use domestic (EN ISO 10874)	<b>Class heavy Residential (Class 23)</b>
Level of use commercial (EN ISO 10874)	<b>Class heavy commercial (Class 33)</b>

### MISC.

Svanen	<b>Yes (3029 0021)</b>
Revision nr	<b>1</b>



woodura®

**Bjelin Sweden AB** | [bjelin.com](http://bjelin.com) | [support@bjelin.com](mailto:support@bjelin.com) | +46-771-101099

Copyright 2026 Bjelin Sweden AB. Weights and dimensions may have minor variations depending on external circumstances. Bjelin reserves the right to deviate from the weight and dimensions in this technical data sheet. Technologies mentioned may be subject to patent protection and invented by Välinge Innovation AB (www.valinge.se/patents). Use of trademarks herein owned by Bjelin Sweden AB or Välinge Innovation AB is under license.



For installation and caring instructions, and further product information, scan the QR code or visit [bjelin.com](http://bjelin.com).