

Woodura Planks 3.0

LOSHULT 3.0 L



Type of wood
Oak



Grading
Select



Surface finishing
Pro matt lacquer



Water resistance
High

Loshult is a white-hued, matt-lacquered hardened wood floor in a Scandinavian design synonymous with minimalism and clean lines. The Misty White shade is crisp and fresh, and the Select grading lends it a calm and pleasant impression. Made from FSC-certified European oak, this class 33 product is extremely durable and ideal for busy spaces like hotels, shops, offices and cafés – or a heavily trafficked area of your home. The matt lacquered finish makes the floor easy to maintain while protecting it from stains.



Specification

GENERAL

Type of floor	Hardened wood
Type of wood	Oak
Grading	Select
Surface finishing	Pro matt lacquer
Staining	Misty White
Light/dark	Light
Pattern	Plank
Locking system	Välinge 5G Dry@
Core	HDF

DIMENSIONS

Format	L
Width	180 mm
Length	2030 mm
Thickness	9,2 mm
Thickness of wear layer	0,6 mm

PACKAGE

Quantity in box	7
m ² / box	2,562 m²
m ² per pallet	92,232 m²
Weight per m ²	8,940 kg
Weight per box	23,06 kg

CLASSIFICATION AND SAFETY

Supports Underfloor Heating	Yes
Water resistance	High
Fire Resistance (EN 13501)	Cfl-s1
Thermal conductivity (EN 12664)	0,12 W/(m*K)
Thermal resistance (EN 12667)	0,075 (m2 x K)/W
Formaldehyde emission (EN 717-1)	E1 <=0.1 ppm (typical value <= 0.05 ppm)
Brinell hardness (EN 1534)	8 HB (average value)
Impact resistance (EN 14354)	EC3
Thickness swelling (EN 14354)	<10% (5% typical)
Wear resistance (EN 14354)	> 6000 cycles
Slip resistance (USRV) (CEN//TS 15676)	40
FSC	FSC Mix (FSC-C140725)
SundaHus	Evaluated by SundaHus
Greenguard Gold	Greenguard Gold Certified
A+	Yes
M1	Yes
CE Marked	Yes
Limited warranty (public environment)	10 years
Limited warranty (home environment)	Limited Lifetime Warranty
Level of use domestic (EN ISO 10874)	Class heavy Residential (Class 23)
Level of use commercial (EN ISO 10874)	Class heavy commercial (Class 33)

MISC.

Revision nr	1
-------------	----------



woodura®

Bjelin bjelin.com support@bjelin.com

Copyright 2026 Bjelin Sweden AB. Weights and dimensions may have minor variations depending on external circumstances. Bjelin reserves the right to deviate from the weight and dimensions in this technical data sheet. Technologies mentioned may be subject to patent protection and invented by Välinge Innovation AB (www.valinge.se/patents). Use of trademarks herein owned by Bjelin Sweden AB or Välinge Innovation AB is under license.



For installation and caring instructions, and further product information, scan the QR code or visit bjelin.com.