

Woodura Planks 3.0

DALEN 3.0 M



Dalen is a Blended (M) product. It is FSC-certified.



Technical Data

Species	Blended
Grade	M
Finish	Välinge 5G Dry®
Core	HDF
Thickness	151 mm
Width	2030 mm
Height	9.2 mm
Surface texture	0,6 mm
Weight per m ²	9,128 kg
Weight per m ³	19,616 kg

Performance Data

Fire Resistance (EN 13501)	Cfl-s1
Thermal conductivity (EN 12664)	0,12 W/(m*K)
Sound absorption (EN 12667)	0,075 (m2 x K)/W
Formaldehyde emission (EN 717-1)	E1 <= 0.1 ppm (typical value <= 0.05 ppm)
Moisture resistance (EN 1534)	8 HB (average value)
Impact resistance (EN 14354)	EC3
Wear resistance (EN 14354)	<10% wear 5% <5%
Scratch resistance (EN 14354)	> 6000 cycles
Slip resistance (USRV) (CEN//TS 15676)	40
FSC	FSC Mix (FSC-C140725)
SundaHus	SundaHus
A+	Yes
M1	Yes
CE	
Warranty	Limited Lifetime Warranty
Class heavy Residential (EN ISO 10874)	Class 23
Class heavy commercial (EN ISO 10874)	Class 33
MISC.	
Revision nr	1



woodura®

Bjelin | bjelin.com | support@bjelin.com | +86 21 522 822 62

Copyright 2026 Bjelin Sweden AB. Weights and dimensions may have minor variations depending on external circumstances. Bjelin reserves the right to deviate from the weight and dimensions in this technical data sheet. Technologies mentioned may be subject to patent protection and invented by Välinge Innovation AB (www.valinge.se/patents). Use of trademarks herein owned by Bjelin Sweden AB or Välinge Innovation AB is under license.



QR code linking to bjelin.com