

# Woodura Planks 3.0

## BOHULT 3.0 M



Type of wood  
Oak



Grading  
Blend



Surface finishing  
Pro matt lacquer



Water resistance  
High

Bohult is a soft-looking, matt-lacquered hardened wood floor in a classic Swedish design. The subtle Earth Grey shade adds calm to a space, and the Blend grading, which includes some colour variations, adds character. Made from FSC-certified European oak, this class 33 product is extremely durable and ideal for heavy-traffic spaces like hotels, shops, offices and cafés – or the entrance of your home. The matt lacquered finish makes the floor easy to maintain while protecting it from stains.



### Specification

#### GENERAL

|                   |                         |
|-------------------|-------------------------|
| Type of floor     | <b>Hardened wood</b>    |
| Type of wood      | <b>Oak</b>              |
| Grading           | <b>Blend</b>            |
| Surface finishing | <b>Pro matt lacquer</b> |
| Staining          | <b>Earth Grey</b>       |
| Light/dark        | <b>Medium dark</b>      |
| Pattern           | <b>Plank</b>            |
| Locking system    | <b>Välinge 5G Dry®</b>  |
| Core              | <b>HDF</b>              |

#### DIMENSIONS

|                                     |                   |
|-------------------------------------|-------------------|
| Format                              | <b>M</b>          |
| Width                               | <b>151 mm</b>     |
| Width (ISO 24337)                   | <b>5.94"</b>      |
| Length                              | <b>2030 mm</b>    |
| Length (ISO 24337)                  | <b>79.92"</b>     |
| Thickness                           | <b>9.2 mm</b>     |
| Thickness (ASTM F387)               | <b>0.36"</b>      |
| Thickness of wear layer             | <b>0,6 mm</b>     |
| Thickness of wear layer (ASTM F410) | <b>0.024"</b>     |
| Weight per m <sup>2</sup>           | <b>20.124 lbs</b> |

#### PACKAGE

|                           |                            |
|---------------------------|----------------------------|
| Quantity in box           | <b>7</b>                   |
| m <sup>2</sup> / box      | <b>2,149 m<sup>2</sup></b> |
| sq.ft per box             | <b>23.132 sqft</b>         |
| m <sup>2</sup> per pallet | <b>96,71 m<sup>2</sup></b> |
| sq.ft per pallet          | <b>1040.98 sqft</b>        |
| Weight per m <sup>2</sup> | <b>9,128 kg</b>            |
| Weight per box            | <b>19,616 kg</b>           |
| Weight per box            | <b>43.246 lbs</b>          |

#### CLASSIFICATION AND SAFETY

|  |   |
|--|---|
| Supports Underfloor Heating            | <b>Yes</b>  |
| Water resistance                       | <b>High</b>   |
| Fire Resistance (EN 13501)             | <b>Cfl-s1</b>   |
| Thermal conductivity (EN 12664)        | <b>0,12 W/(m*K)</b>                                   |
| Thermal resistance (EN 12667)          | <b>0,075 (m2 x K)/W</b>                               |
| Formaldehyde emission (EN 717-1)       | <b>E1 &lt;=0.1 ppm (typical value &lt;= 0.05 ppm)</b> |
| Brinell hardness (EN 1534)             | <b>8 HB (average value)</b>                           |
| Impact resistance (EN 14354)           | <b>EC3</b>  |
| Thickness swelling (EN 14354)          | <b>&lt;10% (5% typical)</b>                           |
| Wear resistance (EN 14354)             | <b>&gt; 6000 cycles</b>                               |
| Slip resistance (USRV) (CEN//TS 15676) | <b>40</b>   |
| FSC                                    | <b>FSC Mix (FSC-C140725)</b>                          |
| SundaHus                               | <b>Evaluated by SundaHus</b>                          |
| A+                                     | <b>Yes</b>  |
| M1                                     | <b>Yes</b>  |
| CE Marked                              | <b>Yes</b>  |
| Limited warranty (public environment)  | <b>10 years</b>                                       |
| Limited warranty (home environment)    | <b>Limited Lifetime Warranty</b>                      |
| Level of use domestic (EN ISO 10874)   | <b>Class heavy Residential (Class 23)</b>             |
| Level of use commercial (EN ISO 10874) | <b>Class heavy commercial (Class 33)</b>              |

#### MISC.

|             |                        |
|-------------|------------------------|
| Svanen      | <b>Yes (3029 0021)</b> |
| Revision nr | <b>1</b>               |



woodura®

**Bjelin Sweden AB** | [bjelin.com](http://bjelin.com) | [support@bjelin.com](mailto:support@bjelin.com) | +46-771-101099

Copyright 2026 Bjelin Sweden AB. Weights and dimensions may have minor variations depending on external circumstances. Bjelin reserves the right to deviate from the weight and dimensions in this technical data sheet. Technologies mentioned may be subject to patent protection and invented by Välinge Innovation AB (www.valinge.se/patents). Use of trademarks herein owned by Bjelin Sweden AB or Välinge Innovation AB is under license.



For installation and caring instructions, and further product information, scan the QR code or visit [bjelin.com](http://bjelin.com).