

Woodura Planks 3.0

YXENHULT 3.0 M



Yxenhult is a Blended (M) product. FSC



Technical Data

Species	Blended
Grade	M
Thickness	151 mm
Width	2030 mm
Length	9.2 mm
Surface texture	0,6 mm
Moisture content	7
Weight per m ²	2,149 kg
Weight per m ³	96,71 kg
Weight per m ²	9,128 kg
Weight per m ³	19,616 kg

Performance Data

Fire Resistance (EN 13501)	Cfl-s1
Sound absorption (EN 12664)	0,12 W/(m ² *K)
Sound insulation (EN 12667)	0,075 (m ² x K)/W
Formaldehyde emission (EN 717-1)	E1 <= 0.01 ppm (typical value <= 0.05 ppm)
Wear resistance (EN 1534)	8 HB (average value)
Stain resistance (EN 14354)	EC3
Scratch resistance (EN 14354)	<10% (5% > 5%)
Slip resistance (USRV) (CEN//TS 15676)	> 6000 cycles
Slip resistance (USRV) (CEN//TS 15676)	40
FSC	FSC Mix (FSC-C140725)
SundaHus	SundaHus
A+	Yes
M1	Yes
CE	
Warranty	10 years
Warranty	Limited Lifetime Warranty
EN ISO 10874	Class heavy Residential (Class 23)
EN ISO 10874	Class heavy commercial (Class 33)
MISC.	
Revision nr	1



woodura®

Bjelin | bjelin.com | support@bjelin.com | +86 21 522 822 62

Copyright 2026 Bjelin Sweden AB. Weights and dimensions may have minor variations depending on external circumstances. Bjelin reserves the right to deviate from the weight and dimensions in this technical data sheet. Technologies mentioned may be subject to patent protection and invented by Välinge Innovation AB (www.valinge.se/patents). Use of trademarks herein owned by Bjelin Sweden AB or Välinge Innovation AB is under license.



www.bjelin.com