

Woodura Planks 3.0

YXENHULT 3.0 M

Type of wood
OakGrading
BlendSurface finishing
Pro Matte finishWater resistance
High

Yxenhult is a hardened wood floor that adds warmth and a sense of luxury to a space. The deep Terra Brown shade adds character and the Blend grading, which includes some color variations, brings out subtle grains. Made from FSC-certified European oak, this class 33 product is extremely durable and ideal for heavy-traffic spaces like hotels, shops, offices and cafés – or the entrance of your home. The commercial matte finish makes the floor easy to maintain while protecting it from stains.



Specification

GENERAL

Type of floor	Hardened wood
Type of wood	Oak
Grading	Blend
Surface finishing	Pro Matte finish
Staining	Terra Brown
Light/dark	Medium dark
Pattern	Plank
Locking system	Välinge 5G Dry®
Core	HDF
Level of use	Commercial

DIMENSIONS

Format	M
Width (ISO 24337)	5.945"
Length (ISO 24337)	79.921"
Thickness (ASTM F387)	0.362"
Thickness of wear layer (ASTM F410)	0.024"
Weight per m ²	20.124 lbs

PACKAGE

Quantity in box	7
sq.ft per box	23.132 sqft
sq.ft per pallet	1040.924 sqft
Weight per sq.ft	1.870 lbs
Weight per box	43.246 lbs

CLASSIFICATION AND SAFETY

Supports Underfloor Heating	Yes
Water resistance	High
Fire Resistance (EN 13501)	Cfl-s1
Thermal conductivity (EN 12664)	0,12 W/(m*K)
Thermal resistance (EN 12667)	0,075 (m2 x K)/W
Formaldehyde emission (EN 717-1)	E1 <=0.1 ppm (typical value <= 0.05 ppm)
Brinell hardness (EN 1534)	8 HB
Impact resistance (EN 14354)	EC3
Thickness swelling (EN 14354)	<10% (5% typical)
Wear resistance (EN 14354)	> 6000 cycles
Slip resistance (USRV) (CEN//TS 15676)	40
FSC	FSC Mix (FSC-C140725)
SundaHus	Evaluated by SundaHus
Svanen	Yes (3029 0032)
A+	Yes
M1	Yes
CE Marked	Yes
Warranty (commercial)	10 years
Warranty (residential)	Limited Lifetime Warranty
Level of use domestic (EN ISO 10874)	Class heavy Residential (Class 23)
Level of use commercial (EN ISO 10874)	Class heavy commercial (Class 33)

MISC.

NOBB-nummer	60903324
Revision nr	1



woodura®

Bjelin | bjelin.com | us-support@bjelin.com

Copyright 2026 Bjelin Sweden AB. Weights and dimensions may have minor variations depending on external circumstances. Bjelin reserves the right to deviate from the weight and dimensions in this technical data sheet. Technologies mentioned may be subject to patent protection and invented by Välinge Innovation AB (www.valinge.se/patents). Use of trademarks herein owned by Bjelin Sweden AB or Välinge Innovation AB is under license.



For installation and caring instructions, and further product information, scan the QR code or visit bjelin.com.