



# Woodura Planks 3.0

## DALSHULT 3.0 XL



A hotel, office, shop or home where you want to offer a welcoming and intriguing ambience. This floor is highly effective in large spaces.



### Specification

**GENERAL**

Type of floor	<b>Hardened wood</b>
Type of wood	<b>Oak</b>
Grading	<b>Nature</b>
Surface finishing	<b>Pro matt lacquer</b>
Staining	<b>Contrast Granite</b>
Light/dark	<b>Light</b>
Pattern	<b>Plank</b>
Locking system	<b>Välinge 5G® Dry™</b>
Core	<b>HDF</b>

**DIMENSIONS**

Format	<b>XL</b>
Width	<b>206 mm</b>
Width (ISO 24337)	<b>8.1"</b>
Length	<b>2200 mm</b>
Length (ISO 24337)	<b>86.6"</b>
Thickness	<b>11 mm</b>
Thickness (ASTM F387)	<b>0.43"</b>
Thickness of wear layer	<b>0,6 mm</b>
Thickness of wear layer (ASTM F410)	<b>0.02"</b>
Weight per m <sup>2</sup>	<b>24 lbs</b>

**PACKAGE**

Quantity in box	<b>4 pcs</b>
m <sup>2</sup> / box	<b>1,81 m<sup>2</sup></b>
sq.ft per box	<b>19.51 sqft</b>
m <sup>2</sup> per pallet	<b>87 m<sup>2</sup></b>
sq.ft per pallet	<b>937 sqft</b>
Weight per m <sup>2</sup>	<b>11 kg</b>
Weight per box	<b>20 kg</b>
Weight per box	<b>44.3 lbs</b>

**CLASSIFICATION AND SAFETY**

Supports Underfloor Heating	<b>Yes</b>
Water resistance	<b>High</b>
Fire Resistance (EN 13501)	<b>Cfl-S1</b>
Thermal conductivity (EN 12664)	<b>0,16 W/(m*K)</b>
Thermal resistance (EN 12667)	<b>0.07 m<sup>2</sup>K/W</b>
Formaldehyde emission (EN 717-1)	<b>E1 &lt;=0.1 ppm (typical value &lt;= 0.05 ppm)</b>
Brinell hardness (EN 1534)	<b>10 HB (average value)</b>
Impact resistance (EN 14354)	<b>EC3</b>
Thickness swelling (EN 14354)	<b>&lt;10% (5% typical)</b>
Wear resistance (EN 14354)	<b>&gt; 6000 cycles</b>
Slip resistance (USRV) (CEN//TS 15676)	<b>40</b>
FSC	<b>FSC Mix</b>
SundaHus	<b>Evaluated by SundaHus</b>
Svanen	<b>Yes (3029 0021)</b>
Greenguard Gold	<b>Greenguard Gold Certified</b>
A+	<b>Yes</b>
M1	<b>Yes</b>
CE Marked	<b>Yes</b>
Limited warranty (public environment)	<b>10 years</b>
Limited warranty (home environment)	<b>Limited Lifetime Warranty</b>
Level of use domestic (EN ISO 10874)	<b>Class heavy Residential (Class 23)</b>
Level of use commercial (EN ISO 10874)	<b>Class heavy commercial (Class 33)</b>



**Bjelin Sweden AB** | [bjelin.com](http://bjelin.com) | [support@bjelin.se](mailto:support@bjelin.se) | +46-771-101099

Copyright 2024 Bjelin Sweden AB. Weights and dimensions may have minor variations depending on external circumstances. Bjelin reserves the right to deviate from the weight and dimensions in this technical data sheet. Technologies mentioned may be subject to patent protection and invented by Välinge Innovation AB (www.valinge.se/patents). Use of trademarks herein owned by Bjelin Sweden AB or Välinge Innovation AB is under license.



For installation and caring instructions, and further product information, scan the QR code or visit [bjelin.com](http://bjelin.com).