


Woodura Planks 3.0

RYA 3.0 XL



Rya es un suelo con un elegante tono plateado que combina a la perfección con nuestros sofisticados grises. Sus acentuadas vetas naturales atraen todas las miradas por su gran carácter, mientras que la gradación Nature garantiza un aspecto de madera auténtica. Fabricado con roble europeo con certificación FSC, este producto de clase 33 ofrece una durabilidad excepcional, ideal para espacios muy transitados como hoteles, tiendas, oficinas y restaurantes, o para la entrada de su hogar. Gracias a su acabado mate barnizado, el suelo es fácil de mantener y resistente a las manchas.



Specification

| GENERAL                 |                  |
|-------------------------|------------------|
| Type of floor           | Hardened wood    |
| Type of wood            | Oak              |
| Grading                 | Nature           |
| Surface finishing       | Pro matt lacquer |
| Staining                | Contrast Silver  |
| Light/dark              | Dark             |
| Pattern                 | Plank            |
| Locking system          | Välinge 5G® Dry™ |
| Core                    | HDF              |
| DIMENSIONS              |                  |
| Format                  | XL               |
| Width                   | 206 mm           |
| Length                  | 2200 mm          |
| Thickness               | 11 mm            |
| Thickness of wear layer | 0,6 mm           |
| PACKAGE                 |                  |
| Quantity in box         | 4 pcs            |
| m² / box                | 1,81 m²          |
| m² per pallet           | 87 m²            |
| Weight per m²           | 11 kg            |
| Weight per box          | 20 kg            |

| CLASSIFICATION AND SAFETY              |                                          |
|----------------------------------------|------------------------------------------|
| Supports Underfloor Heating            | Yes                                      |
| Water resistance                       | High                                     |
| Fire Resistance (EN 13501)             | Cfl-S1                                   |
| Thermal conductivity (EN 12664)        | 0,16 W/(m*K)                             |
| Thermal resistance (EN 12667)          | 0.07 m²K/W                               |
| Formaldehyde emission (EN 717-1)       | E1 <=0.1 ppm (typical value <= 0.05 ppm) |
| Brinell hardness (EN 1534)             | 10 HB (average value)                    |
| Impact resistance (EN 14354)           | EC3                                      |
| Thickness swelling (EN 14354)          | <10% (5% typical)                        |
| Wear resistance (EN 14354)             | > 6000 cycles                            |
| Slip resistance (USRV) (CEN//TS 15676) | 40                                       |
| FSC                                    | FSC Mix (FSC-C140725)                    |
| SundaHus                               | Evaluated by SundaHus                    |
| Greenguard Gold                        | Greenguard Gold Certified                |
| A+                                     | Yes                                      |
| M1                                     | Yes                                      |
| CE Marked                              | Yes                                      |
| Limited warranty (public environment)  | 10 years                                 |
| Limited warranty (home environment)    | Limited Lifetime Warranty                |
| Level of use domestic (EN ISO 10874)   | Class heavy Residential (Class 23)       |
| Level of use commercial (EN ISO 10874) | Class heavy commercial (Class 33)        |



woodura®

Bjelin bjelin.com support@bjelin.com

Copyright 2025 Bjelin Sweden AB. Weights and dimensions may have minor variations depending on external circumstances. Bjelin reserves the right to deviate from the weight and dimensions in this technical data sheet. Technologies mentioned may be subject to patent protection and invented by Välinge Innovation AB (www.valinge.se/patents). Use of trademarks herein owned by Bjelin Sweden AB or Välinge Innovation AB is under license.



For installation and caring instructions, and further product information, scan the QR code or visit [bjelin.com](https://bjelin.com).