

Woodura Planks 3.0

STENESTAD 3.0 XL



Type of wood
Oak



Grading
Rustic



Surface finishing
Hard wax oil



Staining
Misty White



Pattern
Plank



Water resistance
High

Stenestad is a light, hardened wood floor with a hard wax oil surface in a classic Scandi-style. The Misty White shade is the perfect complement for any room, and the Rustic grading provides a lively and powerful sense of wood. Made from FSC-certified European oak, the hard wax oil surface has a natural structure that adds to this wonderful feeling of wood. Due to the maintenance required, we recommend oiled wooden floors in bedrooms and living rooms where there is less heavy traffic. The floors work equally well in busier areas but will require more care in those spaces.



Specification

GENERAL	
Type of floor	Hardened wood
Type of wood	Oak
Grading	Rustic
Surface finishing	Hard wax oil
Staining	Misty White
Light/dark	Light
Pattern	Plank
Locking system	Välinge 5G® Dry™
Core	HDF

DIMENSIONS	
Format	XL
Width	206 mm
Width (ISO 24337)	8.1"
Length	2200 mm
Length (ISO 24337)	86.6"
Thickness	11 mm
Thickness (ASTM F387)	0.43"
Thickness of wear layer	0,6 mm
Thickness of wear layer (ASTM F410)	0.02"
Weight per m²	24 lbs

PACKAGE	
Quantity in box	4 pcs
m² / box	1,81 m²
sq.ft per box	19.51 sqft
m² per pallet	87 m²
sq.ft per pallet	937 sqft
Weight per m²	11 kg
Weight per box	20 kg
Weight per box	44.3 lbs

CLASSIFICATION AND SAFETY	
Supports Underfloor Heating	Yes
Water resistance	High
FSC	FSC Mix
SundaHus	Evaluated by SundaHus
Svanen	Yes (3029 0021)
CE Marked	Yes
Limited warranty (public environment)	10 years
Limited warranty (home environment)	Limited Lifetime Warranty



woodura®

Bjelin Sweden AB | bjelin.com | support@bjelin.se | +46-771-101099

Copyright 2024 Bjelin Sweden AB. Weights and dimensions may have minor variations depending on external circumstances. Bjelin reserves the right to deviate from the weight and dimensions in this technical data sheet. Technologies mentioned may be subject to patent protection and invented by Välinge Innovation AB (www.valinge.se/patents). Use of trademarks herein owned by Bjelin Sweden AB or Välinge Innovation AB is under license.



For installation and caring instructions, and further product information, scan the QR code or visit bjelin.com.