


Woodura Planks 3.0

BONNARP 3.0 XL



Bonnarp is a stylish hardened wood floor in a brushed lacquer that's ideal for subtle tones. This stunning Earth Grey shade has been paired with the Nature grading, providing a natural colour variation in the floor. Made from FSC-certified European oak, the brushed lacquer surface provides a natural wood feel – similar to oiled floors – but the lacquer makes the floors easier to clean and maintain. We recommend brushed lacquered surfaces in all areas of the home.



Specification

GENERAL

Type of floor	Hardened wood
Type of wood	Oak
Grading	Nature
Surface finishing	Brushed lacquer
Staining	Earth Grey
Light/dark	Medium Dark
Pattern	Plank
Locking system	Välinge 5G® Dry™
Core	HDF
Microbevel	4 sided

DIMENSIONS

Format	XL
Width	206 mm
Width (ISO 24337)	8.1"
Length	2200 mm
Length (ISO 24337)	86.6"
Thickness	11 mm
Thickness (ASTM F387)	0.43"
Thickness of wear layer	0,6 mm
Thickness of wear layer (ASTM F410)	0.02"
Weight per m ²	24 lbs

PACKAGE

Quantity in box	4 pcs
m ² / box	1,81 m²
sq.ft. per box	19.51 sqft
m ² per pallet	87 m²
sq.ft. per pallet	937 sqft
Weight per m ²	11 kg
Weight per box	20 kg
Weight per box	44.3 lbs

CLASSIFICATION AND SAFETY

Supports Underfloor Heating	Yes
Water resistance	High
Fire Resistance (EN 13501)	Cfl-S1
Thermal conductivity (EN 12664)	0,16 W/(m*K)
Thermal resistance (EN 12667)	0.07 m²K/W
Formaldehyde emission (EN 717-1)	E1<=0.124 mg/m3
Brinell hardness (EN 1534)	8 HB (average value)
Impact resistance (EN 14354)	EC3
Thickness swelling (EN 14354)	<10% (5% typical)
Wear resistance (EN 14354)	> 1000 cycles
FSC	FSC Mix
SundaHus	Evaluated by SundaHus
Greenguard Gold	Greenguard Gold Certified
A+	Yes
M1	Yes
CE Marked	Yes
Limited warranty (public environment)	10 years
Limited warranty (home environment)	Limited Lifetime Warranty
Level of use domestic (EN ISO 10874)	Class Moderate residential (Class 22)



woodura®

Bjelin Sweden AB | bjelin.com | support@bjelin.se | +46-771-101099

Copyright 2024 Bjelin Sweden AB. Weights and dimensions may have minor variations depending on external circumstances. Bjelin reserves the right to deviate from the weight and dimensions in this technical data sheet. Technologies mentioned may be subject to patent protection and invented by Välinge Innovation AB (www.valinge.se/patents). Use of trademarks herein owned by Bjelin Sweden AB or Välinge Innovation AB is under license.



For installation and caring instructions, and further product information, scan the QR code or visit bjelin.com.