产品数据表| 346027

有关安装和护理说明以及进一步的产品信息，请扫
描QR码，或访问bjelin.com。

Bjelin中国 bjelin.com chinainfo@valinge.se +86 21 522 822 62

Copyright 2025 Bjelin Sweden AB. Weights and dimensions may have minor variations depending on external circumstances. Bjelin reserves the right to deviate from the weight and dimensions in this technical data sheet. Technologies mentioned may be subject to patent protection and invented by Välinge Innovation AB (www.valinge.se/patents). Use of trademarks herein owned by Bjelin Sweden AB or Välinge Innovation AB is under license.

Woodura Planks

3.0

TULLSTORP 3.0 XL

树种
橡木

分级
Nature

表面处理
拉丝漆

颜色选择
TerraBrown

图案
常规板材

防水性
高

Tullstorp是采用拉丝漆的有品位和诱人的硬化木地板。温暖的土褐色色调与Nature (自然)类级相搭配，提供了自然的色彩变化。地板由FSC认证的欧洲橡木制成，拉
丝漆面提供了自然的木质感觉--类似于涂油地板--但漆面使地板更容易清洁和维护。我们建议在家庭的所有区域使用拉丝漆面。

规格

基础信息
地板品类 固化木地板
树种 橡木
分级 Nature
表面处理 拉丝漆
颜色选择 Terra Brown 浅色/深色 Medium Dark
图案 常规板材

锁扣系统 Välinge 5G™Dry™
核芯 HDF
Microbevel 4 sided

尺寸
规格 XL
宽 206 mm 长 2200 mm
高 11 mm
磨损层的厚度 0,6 mm

包装
箱内数量 4件

平⽅⽶/箱 1,81平方米
m² per pallet 87平方米
Weight per m² 11 kg
每箱重量 20 kg

分类和安全属性
⽀持地暖 是
防水性 高

Fire Resistance (EN 13501) Cfl-S1
Thermal conductivity (EN 12664) 0,16 W/(m*K)
Thermal resistance (EN 12667) 0.07 m²K/W Formaldehyde emission (EN 717-1) E1<=0.124 mg/m3 硬度等级(EN 1534) 8 HB (average value)
Impact resistance (EN 14354) EC3
Thickness swelling (EN 14354) <10% (5% typical)
Wear resistance (EN 14354) > 1000 cycles
FSC FSC Mix
SundaHus 由SundaHus评估
Greenguard Gold Greenguard Gold Certified
A+ Yes
M1 Yes
CE认证 是

Limited warranty (public environment) 10年
Limited warranty (home environment) Limited Lifetime Warranty Level of use domestic (EN ISO 10874) Class Moderate residential(Class 22)