

Woodura Planks 3.0

GRYT 3.0 L



Gryt is a timeless, Swedish-designed hardened wood floor with a brushed surface. This authentic-looking wood floor in a Natural shade has been paired with the Blend grading, which includes some colour variations and adds character. Made from FSC-certified European oak, the brushed lacquer surface provides a natural wood feel – similar to oiled floors – but the lacquer makes the floors easier to clean and maintain. We recommend brushed lacquered surfaces in all areas of the home.



Specification

GENERAL

Type of floor	Hardened wood
Type of wood	Oak
Grading	Blend
Surface finishing	Brushed lacquer
Staining	Natural
Light/dark	Light
Pattern	Plank
Locking system	Välinge 5G® Dry™
Core	HDF

DIMENSIONS

Format	L
Width	180 mm
Width (ISO 24337)	7.09"
Length	2000 mm
Length (ISO 24337)	78.74"
Thickness	9 mm
Thickness (ASTM F387)	0.35"
Thickness of wear layer	0,6 mm
Thickness of wear layer (ASTM F410)	0.024"
Weight per m ²	19.9 lbs

PACKAGE

Quantity in box	7
m ² / box	2,5 m²
sq.ft per box	271 sqft
m ² per pallet	90,7 m²
sq.ft per pallet	976.5 sqft
Weight per m ²	9 kg
Weight per box	22,7 kg
Weight per box	50.1 lbs

CLASSIFICATION AND SAFETY

Supports Underfloor Heating	Yes
Water resistance	High
Fire Resistance (EN 13501)	Cfl-S1
Thermal conductivity (EN 12664)	0,12 W/(m*K)
Thermal resistance (EN 12667)	0,075 (m2 x K)/W
Formaldehyde emission (EN 717-1)	E1 <=0.1 ppm (typical value <= 0.05 ppm)
Brinell hardness (EN 1534)	8 HB (average value)
Impact resistance (EN 14354)	EC3
Thickness swelling (EN 14354)	<10% (5% typical)
Wear resistance (EN 14354)	> 1000 cycles
Slip resistance (USRV) (CEN//TS 15676)	40
FSC	FSC Mix
A+	Yes
M1	Yes
CE Marked	Yes
Limited warranty (public environment)	10 years
Limited warranty (home environment)	Limited Lifetime Warranty
Level of use domestic (EN ISO 10874)	Class Moderate residential (Class 22)



woodura®

Bjelin Sweden AB | bjelin.com | support@bjelin.se | +46-771-101099

Copyright 2024 Bjelin Sweden AB. Weights and dimensions may have minor variations depending on external circumstances. Bjelin reserves the right to deviate from the weight and dimensions in this technical data sheet. Technologies mentioned may be subject to patent protection and invented by Välinge Innovation AB (www.valinge.se/patents). Use of trademarks herein owned by Bjelin Sweden AB or Välinge Innovation AB is under license.



For installation and caring instructions, and further product information, scan the QR code or visit bjelin.com.