

Woodura Planks 3.0

EKET 3.0 L



A room where you want a natural wood feeling and endless interior design choices. The Natural shade offers the exquisite look of newly cut timber, bringing out a true feeling of nature in the floors.



Specification

GENERAL

Type of floor	Hardened wood
Type of wood	Oak
Grading	Nature
Surface finishing	Brushed lacquer
Staining	Natural
Light/dark	Medium Dark
Pattern	Plank
Locking system	Välinge 5G® Dry™
Core	HDF

DIMENSIONS

Format	L
Width	180 mm
Length	2000 mm
Thickness	9 mm
Thickness of wear layer	0,6 mm

PACKAGE

Quantity in box	7
m² / box	2,5 m²
m² per pallet	90,7 m²
Weight per m²	9 kg
Weight per box	22,7 kg

CLASSIFICATION AND SAFETY

Supports Underfloor Heating	Yes
Water resistance	High
Fire Resistance (EN 13501)	Cfl-S1
Thermal conductivity (EN 12664)	0,12 W/(m*K)
Thermal resistance (EN 12667)	0,075 (m2 x K)/W
Formaldehyde emission (EN 717-1)	E1 <=0.1 ppm (typical value <= 0.05 ppm)
Brinell hardness (EN 1534)	8 HB (average value)
Impact resistance (EN 14354)	EC3
Thickness swelling (EN 14354)	<10% (5% typical)
Wear resistance (EN 14354)	> 1000 cycles
Slip resistance (USRV) (CEN//TS 15676)	40
FSC	FSC Mix (FSC-C140725)
A+	Yes
M1	Yes
CE Marked	Yes
Limited warranty (public environment)	10 years
Limited warranty (home environment)	Limited Lifetime Warranty
Level of use domestic (EN ISO 10874)	Class Moderate residential (Class 22)



woodura®

Bjelin bjelin.com uk-sales@bjelin.com

Copyright 2025 Bjelin Sweden AB. Weights and dimensions may have minor variations depending on external circumstances. Bjelin reserves the right to deviate from the weight and dimensions in this technical data sheet. Technologies mentioned may be subject to patent protection and invented by Välinge Innovation AB (www.valinge.se/patents). Use of trademarks herein owned by Bjelin Sweden AB or Välinge Innovation AB is under license.



For installation and caring instructions, and further product information, scan the QR code or visit bjelin.com.