

# Woodura Planks 3.0

## VALJE 3.0 L



Type of wood  
Oak



Grading  
Blend



Surface finishing  
Brushed lacquer



Staining  
Powder White



Pattern  
Plank



Water resistance  
High

Valje is a beautiful hardened wood floor in a clean-looking Powder White shade, paired with the Blend grading, which offers some colour variations and adds character. Made from FSC-certified European oak, the brushed lacquer surface provides a natural wood feel – similar to oiled floors – but the lacquer makes the floors easier to clean and maintain. We recommend brushed lacquered surfaces in all areas of the home.



## Specification

### GENERAL

|                   |                         |
|-------------------|-------------------------|
| Type of floor     | <b>Hardened wood</b>    |
| Type of wood      | <b>Oak</b>              |
| Grading           | <b>Blend</b>            |
| Surface finishing | <b>Brushed lacquer</b>  |
| Staining          | <b>Powder White</b>     |
| Light/dark        | <b>Light</b>            |
| Pattern           | <b>Plank</b>            |
| Locking system    | <b>Välinge 5G® Dry™</b> |
| Core              | <b>HDF</b>              |

### DIMENSIONS

|                                     |                 |
|-------------------------------------|-----------------|
| Format                              | <b>L</b>        |
| Width                               | <b>180 mm</b>   |
| Width (ISO 24337)                   | <b>7.09"</b>    |
| Length                              | <b>2000 mm</b>  |
| Length (ISO 24337)                  | <b>78.74"</b>   |
| Thickness                           | <b>9 mm</b>     |
| Thickness (ASTM F387)               | <b>0.35"</b>    |
| Thickness of wear layer             | <b>0,6 mm</b>   |
| Thickness of wear layer (ASTM F410) | <b>0.024"</b>   |
| Weight per m <sup>2</sup>           | <b>19.9 lbs</b> |

### PACKAGE

|                           |                           |
|---------------------------|---------------------------|
| Quantity in box           | <b>7</b>                  |
| m <sup>2</sup> / box      | <b>2,5 m<sup>2</sup></b>  |
| sq.ft per box             | <b>271 sqft</b>           |
| m <sup>2</sup> per pallet | <b>90,7 m<sup>2</sup></b> |
| sq.ft per pallet          | <b>976.5 sqft</b>         |
| Weight per m <sup>2</sup> | <b>9 kg</b>               |
| Weight per box            | <b>22,7 kg</b>            |
| Weight per box            | <b>50.1 lbs</b>           |

### CLASSIFICATION AND SAFETY

|  |   |
|--|---|
| Supports Underfloor Heating            | <b>Yes</b>  |
| Water resistance                       | <b>High</b>   |
| Fire Resistance (EN 13501)             | <b>Cfl-S1</b>   |
| Thermal conductivity (EN 12664)        | <b>0,12 W/(m*K)</b>                                   |
| Thermal resistance (EN 12667)          | <b>0,075 (m2 x K)/W</b>                               |
| Formaldehyde emission (EN 717-1)       | <b>E1 &lt;=0.1 ppm (typical value &lt;= 0.05 ppm)</b> |
| Brinell hardness (EN 1534)             | <b>8 HB (average value)</b>                           |
| Impact resistance (EN 14354)           | <b>EC3</b>  |
| Thickness swelling (EN 14354)          | <b>&lt;10% (5% typical)</b>                           |
| Wear resistance (EN 14354)             | <b>&gt; 1000 cycles</b>                               |
| Slip resistance (USRV) (CEN//TS 15676) | <b>40</b>   |
| FSC                                    | <b>FSC Mix</b>  |
| A+                                     | <b>Yes</b>  |
| M1                                     | <b>Yes</b>  |
| CE Marked                              | <b>Yes</b>  |
| Limited warranty (public environment)  | <b>10 years</b>                                       |
| Limited warranty (home environment)    | <b>Limited Lifetime Warranty</b>                      |
| Level of use domestic (EN ISO 10874)   | <b>Class Moderate residential (Class 22)</b>          |



woodura®

**Bjelin Sweden AB** | [bjelin.com](http://bjelin.com) | [support@bjelin.se](mailto:support@bjelin.se) | +46-771-101099

Copyright 2024 Bjelin Sweden AB. Weights and dimensions may have minor variations depending on external circumstances. Bjelin reserves the right to deviate from the weight and dimensions in this technical data sheet. Technologies mentioned may be subject to patent protection and invented by Välinge Innovation AB ([www.valinge.se/patents](http://www.valinge.se/patents)). Use of trademarks herein owned by Bjelin Sweden AB or Välinge Innovation AB is under license.



For installation and caring instructions, and further product information, scan the QR code or visit [bjelin.com](http://bjelin.com).