


Woodura Planks 3.0

TULLSTORP 3.0 L



Tullstorp er et rikt og innbydende herdet tregulv i børstet lakk. Den varme Terra Brown-nyansen er kombinert med Nature-sorteringen, noe som gir noen naturlige fargevariasjoner. Den børstede lakkoverflaten er laget av FSC-sertifisert europeisk eik og gir en naturlig trefølelse - i likhet med oljede gulv - men lakken gjør gulvene enklere å rengjøre og vedlikeholde. Vi anbefaler børstede lakkerte overflater til de fleste rommene av hjemmet.



Specification

GENERAL	
Type of floor	Hardened wood
Type of wood	Oak
Grading	Nature
Surface finishing	Brushed lacquer
Staining	Terra Brown
Light/dark	Dark
Pattern	Plank
Locking system	5G Dry®
Core	HDF
DIMENSIONS	
Format	L
Width	180 mm
Length	2000 mm
Thickness	9 mm
Thickness of wear layer	0,6 mm
PACKAGE	
Quantity in box	7
m² / box	2,5 m²
m² per pallet	90,7 m²
Weight per m²	9 kg
Weight per box	22,7 kg

CLASSIFICATION AND SAFETY	
Supports Underfloor Heating	Yes
Water resistance	High
Fire Resistance (EN 13501)	Cfl-S1
Thermal conductivity (EN 12664)	0,12 W/(m*K)
Thermal resistance (EN 12667)	0,075 (m2 x K)/W
Formaldehyde emission (EN 717-1)	E1 <=0.1 ppm (typical value <= 0.05 ppm)
Brinell hardness (EN 1534)	8 HB (average value)
Impact resistance (EN 14354)	EC3
Thickness swelling (EN 14354)	<10% (5% typical)
Wear resistance (EN 14354)	> 1000 cycles
Slip resistance (USRV) (CEN//TS 15676)	40
FSC	FSC Mix (FSC-C140725)
A+	Yes
M1	Yes
CE Marked	Yes
Limited warranty (public environment)	30 years
Limited warranty (home environment)	30 years
Level of use domestic (EN ISO 10874)	Class Moderate residential (Class 22)



woodura®

Bjelin bjelin.com support@bjelin.com +47 3322 2300

Copyright 2025 Bjelin Sweden AB. Weights and dimensions may have minor variations depending on external circumstances. Bjelin reserves the right to deviate from the weight and dimensions in this technical data sheet. Technologies mentioned may be subject to patent protection and invented by Välinge Innovation AB (www.valinge.se/patents). Use of trademarks herein owned by Bjelin Sweden AB or Välinge Innovation AB is under license.



For installation and caring instructions, and further product information, scan the QR code or visit bjelin.com.