

Woodura Planks 3.0

## GRYT 3.0 M

Type of wood  
OakGrading  
BlendSurface finishing  
Brushed finishWater resistance  
High

Gryt is a timeless hardened wood floor with a brushed surface, which is comfortable underfoot. The Natural shade has been paired with a Blend grading for an authentic appearance. Crafted from responsibly sourced FSC®-certified European oak, the brushed finish provides a natural wood feel – similar to oiled floors – with the added benefit of being easier to clean and maintain. Brushed surfaces are ideal for most areas of the home.



## Specification

## GENERAL

|                   |                      |
|-------------------|----------------------|
| Type of floor     | Hardened wood        |
| Type of wood      | Oak                  |
| Grading           | Blend                |
| Surface finishing | Brushed finish       |
| Staining          | Natural              |
| Light/dark        | Medium dark          |
| Pattern           | Plank                |
| Locking system    | 5G Dry®              |
| Core              | HDF                  |
| Microbevel        | long- and short side |

## DIMENSIONS

|                                     |            |
|-------------------------------------|------------|
| Format                              | M          |
| Width (ISO 24337)                   | 5.945"     |
| Length (ISO 24337)                  | 79.921"    |
| Thickness (ASTM F387)               | 0.362"     |
| Thickness of wear layer (ASTM F410) | 0.024"     |
| Weight per m²                       | 20.124 lbs |

## PACKAGE

|                  |               |
|------------------|---------------|
| Quantity in box  | 7             |
| sq.ft per box    | 23.132 sqft   |
| sq.ft per pallet | 1040.924 sqft |
| Weight per sq.ft | 1.870 lbs     |
| Weight per box   | 43.246 lbs    |

## CLASSIFICATION AND SAFETY

|                                           |                                               |
|-------------------------------------------|-----------------------------------------------|
| Supports Underfloor Heating               | Yes                                           |
| Water resistance                          | High                                          |
| Fire Resistance (EN 13501)                | Cfl-S1                                        |
| Thermal conductivity (EN 12664)           | 0,16 W/(m²K)                                  |
| Thermal resistance (EN 12667)             | 0.07 m²K/W                                    |
| Formaldehyde emission (EN 717-1)          | E1 <=0.1 ppm (typical value <= 0.05 ppm)      |
| Brinell hardness (EN 1534)                | 8 HB                                          |
| Impact resistance (EN 14354)              | EC3                                           |
| Thickness swelling (EN 14354)             | <10% (5% typical)                             |
| Wear resistance (EN 14354)                | > 1000 cycles                                 |
| Slip resistance (USRV)<br>(CEN//TS 15676) | EU: With slider 55: 78 GB: With slider 96: 65 |
| FSC                                       | FSC Mix (FSC-C140725)                         |
| A+                                        | Yes                                           |
| M1                                        | Yes                                           |
| CE Marked                                 | Yes                                           |
| Warranty (commercial)                     | 10 years                                      |
| Warranty (residential)                    | Limited Lifetime Warranty                     |
| Level of use domestic<br>(EN ISO 10874)   | Class Moderate residential (Class 22)         |

## MISC.

|             |          |
|-------------|----------|
| NOBB-number | 60820357 |
|-------------|----------|



woodura®

Bjelin bjelin.com us-support@bjelin.com

Copyright 2026 Bjelin Sweden AB. Weights and dimensions may have minor variations depending on external circumstances. Bjelin reserves the right to deviate from the weight and dimensions in this technical data sheet. Technologies mentioned may be subject to patent protection and invented by Välinge Innovation AB (www.valinge.se/patents). Use of trademarks herein owned by Bjelin Sweden AB or Välinge Innovation AB is under license.



For installation and caring instructions, and further product information, scan the QR code or visit [bjelin.com](http://bjelin.com).