

Woodura Planks 3.0

LYNGBY 3.0 M

Treslag
EikSortering
BlendOverflatebehandling
Børstet mattlakkInnfarging
Misty WhiteMønster
PlankVannbestandighet
Høy

Spesifikasjon

GENERELT

Type gulv	Herdet tregulv
Treslag	Eik
Sortering	Blend
Overflatebehandling	Børstet mattlakk
Innfarging	Misty White
Lyst/mørkt	Lyst
Mønster	Plank
Fug	5G Dry®
Kjerne	HDF
Mikrobevel	long- and short side

MÅL

Format	M
Bredde	151 mm
Lengde	2030 mm
Høyde	9 mm
Slitesjiktets tykkelse	0,6 mm

EMBALLASJE

Antall i pakken	7
m² i pakken	2,149 m²
m² per pall	95,13 m²
Vekt pr. m2	9 kg
Vekt pr. pakke	20 kg

KLASSIFISERING OG SIKKERHET

Egnet for gulvvarme	Ja
Vannbestandighet	Høy
Motstandsyktighet mot brann (EN 13501)	Cfl-S1
Termisk ledningsevne (EN 12664)	0,16 W/(m*K)
Termisk motstand (EN 12667)	0,07 m²K/W
Formaldehyd emisjon (EN 717-1)	E1 <= 0,1 ppm (type verdi <= 0,05 ppm)
Brinellhardhet (EN 1534)	8 HB (average value)
Slagfasthet (EN 14354)	EC3
Svellingsgrad (EN 14354)	<10% (5% type verdi)
Slitestykke (EN 14354)	> 1000 cycles
Sklisikkerhet (USRV) (CEN//TS 15676)	EU: With slider 55: 78 GB: With slider 96: 65
FSC	FSC Mix (FSC-C140725)
A+	Yes
M1	Yes
CE-merket	Ja
Garanti (offentlige miljø)	30 år
Garanti (private hjem)	30 år
Slitestykke i private hjem (EN ISO 10874)	Class Moderate residential (Class 22)

ANNEN

NOBB-nummer	60820358
-------------	----------



woodura®

Bjelin bjelin.com support@bjelin.com +47 3322 2300

Copyright 2025 Bjelin Sweden AB. Weights and dimensions may have minor variations depending on external circumstances. Bjelin reserves the right to deviate from the weight and dimensions in this technical data sheet. Technologies mentioned may be subject to patent protection and invented by Vålinge Innovation AB (www.valinge.se/patents). Use of trademarks herein owned by Bjelin Sweden AB or Vålinge Innovation AB is under license.



Skann QR-koden med mobilen eller besøk bjelin.com for å se informasjon om legging og ytterligere produktinformasjon.