

Woodura Planks 3.0

VALJE 3.0 M



Type of wood
Oak



Grading
Blend



Surface finishing
Brushed lacquer



Staining
Powder White



Pattern
Plank



Water resistance
High

A room where you want to add light. The Powder White shade is a popular choice in a modern setting since it creates an open and airy feeling.



Specification

GENERAL

Type of floor	Hardened wood
Type of wood	Oak
Grading	Blend
Surface finishing	Brushed lacquer
Staining	Powder White
Light/dark	Light
Pattern	Plank
Locking system	5G Dry®
Core	HDF
Microbevel	long- and short side

DIMENSIONS

Format	M
Width	151 mm
Width (ISO 24337)	5.94"
Length	2030 mm
Length (ISO 24337)	79.92"
Thickness	9 mm
Thickness (ASTM F387)	0.35"
Thickness of wear layer	0,6 mm
Thickness of wear layer (ASTM F410)	0.024"
Weight per m²	19.9 lbs

PACKAGE

Quantity in box	7
m² / box	2,149 m²
sq.ft per box	23.1 sqft
m² per pallet	95,13 m²
sq.ft per pallet	1024 sqft
Weight per m²	9 kg
Weight per box	20 kg
Weight per box	44 lbs

CLASSIFICATION AND SAFETY

Supports Underfloor Heating	Yes
Water resistance	High
Fire Resistance (EN 13501)	Cfl-S1
Thermal conductivity (EN 12664)	0,16 W/(m²K)
Thermal resistance (EN 12667)	0.07 m²K/W
Formaldehyde emission (EN 717-1)	E1 <=0.1 ppm (typical value <= 0.05 ppm)
Brinell hardness (EN 1534)	8 HB (average value)
Impact resistance (EN 14354)	EC3
Thickness swelling (EN 14354)	<10% (5% typical)
Wear resistance (EN 14354)	> 1000 cycles
Slip resistance (USRV) (CEN//TS 15676)	EU: With slider 55: 78 GB: With slider 96: 65
FSC	FSC Mix (FSC-C140725)
A+	Yes
M1	Yes
CE Marked	Yes
Limited warranty (public environment)	10 years
Limited warranty (home environment)	Limited Lifetime Warranty
Level of use domestic (EN ISO 10874)	Class Moderate residential (Class 22)



woodura®

Bjelin Sweden AB bjelin.com support@bjelin.com +46-771-101099

Copyright 2025 Bjelin Sweden AB. Weights and dimensions may have minor variations depending on external circumstances. Bjelin reserves the right to deviate from the weight and dimensions in this technical data sheet. Technologies mentioned may be subject to patent protection and invented by Vålinge Innovation AB (www.valinge.se/patents). Use of trademarks herein owned by Bjelin Sweden AB or Vålinge Innovation AB is under license.



For installation and caring instructions, and further product information, scan the QR code or visit bjelin.com.