

Woodura Planks 3.0

VALJE 3.0 M



Type of wood  
Oak



Grading  
Blend



Surface finishing  
Brushed lacquer



Staining  
Powder White



Pattern  
Plank



Water resistance  
High

A room where you want to add light. The Powder White shade is a popular choice in a modern setting since it creates an open and airy feeling.



Specification

| GENERAL                 |                      |
|-------------------------|----------------------|
| Type of floor           | Hardened wood        |
| Type of wood            | Oak                  |
| Grading                 | Blend                |
| Surface finishing       | Brushed lacquer      |
| Staining                | Powder White         |
| Light/dark              | Light                |
| Pattern                 | Plank                |
| Locking system          | 5G Dry®              |
| Core                    | HDF                  |
| Microbevel              | long- and short side |
| DIMENSIONS              |                      |
| Format                  | M                    |
| Width                   | 151 mm               |
| Length                  | 2030 mm              |
| Thickness               | 9 mm                 |
| Thickness of wear layer | 0,6 mm               |
| PACKAGE                 |                      |
| Quantity in box         | 7                    |
| m² / box                | 2,149 m²             |
| m² per pallet           | 95,13 m²             |
| Weight per m²           | 9 kg                 |
| Weight per box          | 20 kg                |

| CLASSIFICATION AND SAFETY                 |                                               |
|-------------------------------------------|-----------------------------------------------|
| Supports Underfloor Heating               | Yes                                           |
| Water resistance                          | High                                          |
| Fire Resistance (EN 13501)                | Cfl-S1                                        |
| Thermal conductivity (EN 12664)           | 0,16 W/(m²K)                                  |
| Thermal resistance (EN 12667)             | 0.07 m²K/W                                    |
| Formaldehyde emission (EN 717-1)          | E1 <=0.1 ppm (typical value <= 0.05 ppm)      |
| Brinell hardness (EN 1534)                | 8 HB (average value)                          |
| Impact resistance (EN 14354)              | EC3                                           |
| Thickness swelling (EN 14354)             | <10% (5% typical)                             |
| Wear resistance (EN 14354)                | > 1000 cycles                                 |
| Slip resistance (USRV)<br>(CEN//TS 15676) | EU: With slider 55: 78 GB: With slider 96: 65 |
| FSC                                       | FSC Mix (FSC-C140725)                         |
| A+                                        | Yes                                           |
| M1                                        | Yes                                           |
| CE Marked                                 | Yes                                           |
| Limited warranty (public environment)     | 10 years                                      |
| Limited warranty (home environment)       | Limited Lifetime Warranty                     |
| Level of use domestic<br>(EN ISO 10874)   | Class Moderate residential (Class 22)         |



woodura®

Bjelin bjelin.com support@bjelin.com

Copyright 2025 Bjelin Sweden AB. Weights and dimensions may have minor variations depending on external circumstances. Bjelin reserves the right to deviate from the weight and dimensions in this technical data sheet. Technologies mentioned may be subject to patent protection and invented by Välinge Innovation AB (www.valinge.se/patents). Use of trademarks herein owned by Bjelin Sweden AB or Välinge Innovation AB is under license.



For installation and caring instructions, and further product information, scan the QR code or visit [bjelin.com](https://bjelin.com).