

Woodura Planks 3.0

DYVIK 3.0 M

Vrsta drveta
HrastKlase
BlendPovršinska obrada
Četkani mat lakOtpornost na vodu
Visoka

Dyvik je učvršćeni drveni pod s četkanom površinom koja prirodno pruža udobnost pod nogama. Topla nijansa Terra Brown u kombinaciji s klasom Blend unosi prirodne varijacije boje i izražajan karakter drveta. Izrađen je od odgovorno nabavljenog, FSC®-certificiranog europskog hrasta. Četkani lakirani završni sloj pruža prirodan osjećaj drveta – sličan uljenim podovima – uz prednost jednostavnijeg čišćenja i održavanja. Površine s četkanim lakom idealne su za većinu prostorija u domu.



Specifikacija

OPĆENITO

Vrsta podne obloge	Učvršćeno drvo
Vrsta drveta	Hrast
Klase	Blend
Površinska obrada	Četkani mat lak
Boja	Terra Brown
Svijetlo/tamno	Tamno
Uzorak	Podna daska
Spoj	5G Dry@
Jezgra	HDF
Mikrobevel	long- and short side

DIMENZIJE

Format	M
Širina	151 mm
Dužina	2030 mm
Visina	9 mm
Debljina gornjeg sloja	0,6 mm

PAKET

Količina u paketu	7
m ² / paket	2,149 m ²
m ² po paleti	95,13 m ²
Težina po m ²	9 kg
Težina po paketu	20 kg

KLASIFIKACIJA I SIGURNOST

Podržava podno grijanje	Da
Otpornost na vodu	Visoka
Otpornost na vatru (EN 13501)	Cfl-S1
Toplinska vodljivost (EN 12664)	0,16 W/(m*K)
Toplinska otpornost (EN 12667)	0,07 m ² K/W
Emisija formaldehida (EN 717-1)	Emisija formaldehida.E1 <=0,1 ppm (tipična vrijednost <= 0,05 ppm)
Ocjena tvrdoće (EN 1534)	8 HB (average value)
Otpornost na udarce (EN 14354)	EC3
Debljina oticanja (EN 14354)	<10% (5% tipično)
Otpornost na habanje (EN 14354)	> 1000 ciklusa
Otpor na klizanje (USRV) (CEN//TS 15676)	EU: With slider 55: 78 GB: With slider 96: 65
FSC	FSC Mix (FSC-C140725)
A+	Yes
M1	Yes
CE označeno	Da
Ograničeno jamstvo (javno okruženje)	30 godine
Ograničeno jamstvo (kućno okruženje)	30 godine
Razina kućne upotrebe (EN ISO 10874)	Class Moderate residential (Class 22)



woodura®

Bjelin Croatia d.o.o | bjelin.com | hr-sales@bjelin.com

Copyright 2026 Bjelin Sweden AB. Weights and dimensions may have minor variations depending on external circumstances. Bjelin reserves the right to deviate from the weight and dimensions in this technical data sheet. Technologies mentioned may be subject to patent protection and invented by Välinge Innovation AB (www.valinge.se/patents). Use of trademarks herein owned by Bjelin Sweden AB or Välinge Innovation AB is under license.



Za upute o postavljanju i održavanju te daljnje informacije o proizvodu skenirajte QR kod ili posjetite bjelin.com.