

Woodura Planks 3.0

DYVIK 3.0 M

Type of wood
OakGrading
BlendSurface finishing
Brushed finishWater resistance
High

Dyvik is a hardened wood floor with a brushed surface, which is naturally comfortable underfoot. The warm Terra Brown shade has been combined with the Blend grading to add some natural color variations and character. Crafted from responsibly sourced FSC®-certified European oak, the brushed finish provides a natural wood feel – similar to oiled floors – with the added benefit of being easier to clean and maintain. Brushed surfaces are ideal for most areas of the home.



Specification

GENERAL

Type of floor	Hardened wood
Type of wood	Oak
Grading	Blend
Surface finishing	Brushed finish
Staining	Terra Brown
Light/dark	Dark
Pattern	Plank
Locking system	5G Dry®
Core	HDF
Microbevel	long- and short side

DIMENSIONS

Format	M
Width (ISO 24337)	5.945"
Length (ISO 24337)	79.921"
Thickness (ASTM F387)	0.362"
Thickness of wear layer (ASTM F410)	0.024"
Weight per m ²	20.124 lbs

PACKAGE

Quantity in box	7
sq.ft per box	23.132 sqft
sq.ft per pallet	1040.924 sqft
Weight per sq.ft	1.870 lbs
Weight per box	43.246 lbs

CLASSIFICATION AND SAFETY

Supports Underfloor Heating	Yes
Water resistance	High
Fire Resistance (EN 13501)	Cfl-S1
Thermal conductivity (EN 12664)	0,16 W/(m*K)
Thermal resistance (EN 12667)	0.07 m²K/W
Formaldehyde emission (EN 717-1)	E1 <=0.1 ppm (typical value <= 0.05 ppm)
Brinell hardness (EN 1534)	8 HB
Impact resistance (EN 14354)	EC3
Thickness swelling (EN 14354)	<10% (5% typical)
Wear resistance (EN 14354)	> 1000 cycles
Slip resistance (USRV) (CEN//TS 15676)	EU: With slider 55: 78 GB: With slider 96: 65
FSC	FSC Mix (FSC-C140725)
A+	Yes
M1	Yes
CE Marked	Yes
Warranty (commercial)	10 years
Warranty (residential)	Limited Lifetime Warranty
Level of use domestic (EN ISO 10874)	Class Moderate residential (Class 22)

MISC.

NOBB-number	60820380
-------------	----------



woodura®

Bjelin bjelin.com us-support@bjelin.com

Copyright 2026 Bjelin Sweden AB. Weights and dimensions may have minor variations depending on external circumstances. Bjelin reserves the right to deviate from the weight and dimensions in this technical data sheet. Technologies mentioned may be subject to patent protection and invented by Vålinge Innovation AB (www.valinge.se/patents). Use of trademarks herein owned by Bjelin Sweden AB or Vålinge Innovation AB is under license.



For installation and caring instructions, and further product information, scan the QR code or visit bjelin.com.