

Woodura Planks 3.0

HÖJA 3.0 L



Type of wood
Oak



Grading
Nature



Surface finishing
Brushed lacquer



Water resistance
High

A room that could benefit from a light and versatile colour. Misty White is a welcoming and warm shade that creates a lovely sense of space.



Specification

GENERAL

| | |
|-------------------|------------------------|
| Type of floor | Hardened wood |
| Type of wood | Oak |
| Grading | Nature |
| Surface finishing | Brushed lacquer |
| Staining | Misty White |
| Light/dark | Light |
| Pattern | Plank |
| Locking system | Välinge 5G Dry® |
| Core | HDF |

DIMENSIONS

| | |
|-------------------------|----------------|
| Format | L |
| Width | 180 mm |
| Length | 2030 mm |
| Thickness | 9,2 mm |
| Thickness of wear layer | 0,6 mm |

PACKAGE

| | |
|---------------------------|-----------------------------|
| Quantity in box | 7 |
| m ² / box | 2,562 m² |
| m ² per pallet | 92,232 m² |
| Weight per m ² | 8,940 kg |
| Weight per box | 23,06 kg |

CLASSIFICATION AND SAFETY

| | |
|--|---|
| Supports Underfloor Heating | Yes |
| Water resistance | High |
| Fire Resistance (EN 13501) | Cfl-S1 |
| Thermal conductivity (EN 12664) | 0,12 W/(m*K) |
| Thermal resistance (EN 12667) | 0,075 (m2 x K)/W |
| Formaldehyde emission (EN 717-1) | E1 <=0.1 ppm (typical value <= 0.05 ppm) |
| Brinell hardness (EN 1534) | 8 HB (average value) |
| Impact resistance (EN 14354) | EC3 |
| Thickness swelling (EN 14354) | <10% (5% typical) |
| Wear resistance (EN 14354) | > 1000 cycles |
| Slip resistance (USRV) (CEN//TS 15676) | 40 |
| FSC | FSC Mix (FSC-C140725) |
| A+ | Yes |
| M1 | Yes |
| CE Marked | Yes |
| Limited warranty (public environment) | 10 years |
| Limited warranty (home environment) | Limited Lifetime Warranty |
| Level of use domestic (EN ISO 10874) | Class Moderate residential (Class 22) |

MISC.

| | |
|-------------|----------|
| Revision nr | 1 |
|-------------|----------|



woodura®

Bjelin bjelin.com support@bjelin.com

Copyright 2026 Bjelin Sweden AB. Weights and dimensions may have minor variations depending on external circumstances. Bjelin reserves the right to deviate from the weight and dimensions in this technical data sheet. Technologies mentioned may be subject to patent protection and invented by Välinge Innovation AB (www.valinge.se/patents). Use of trademarks herein owned by Bjelin Sweden AB or Välinge Innovation AB is under license.



For installation and caring instructions, and further product information, scan the QR code or visit bjelin.com.