


# Woodura Planks 3.0

## GANTOFTA 3.0 XL



Gantofta is a rich-looking, matt-lacquered hardened wood floor that brings the authentic feel of wood into your home. Terra Brown is synonymous with nature, and the appropriately named Nature grading adds to this classic feeling of wood. Made from FSC-certified European oak, this class 33 product is extremely durable and ideal for busy spaces like hotels, shops, offices and cafés – or a heavily trafficked area of your home. The matt lacquered finish makes the floor easy to maintain while protecting it from stains.



### Specification

#### GENERAL

Type of floor	<b>Hardened wood</b>
Type of wood	<b>Oak</b>
Grading	<b>Nature</b>
Surface finishing	<b>Pro matt lacquer</b>
Staining	<b>Terra Brown</b>
Light/dark	<b>Dark</b>
Pattern	<b>Plank</b>
Locking system	<b>Välinge 5G® Dry™</b>
Core	<b>HDF</b>

#### DIMENSIONS

Format	<b>XL</b>
Width	<b>206 mm</b>
Width (ISO 24337)	<b>8.1"</b>
Length	<b>2200 mm</b>
Length (ISO 24337)	<b>86.6"</b>
Thickness	<b>11 mm</b>
Thickness (ASTM F387)	<b>0.43"</b>
Thickness of wear layer	<b>0,6 mm</b>
Thickness of wear layer (ASTM F410)	<b>0.02"</b>

#### PACKAGE

Quantity in box	<b>4 pcs</b>
m <sup>2</sup> / box	<b>1,81 m<sup>2</sup></b>
sq.ft per box	<b>19.51 sqft</b>
m <sup>2</sup> per pallet	<b>87 m<sup>2</sup></b>
sq.ft per pallet	<b>937 sqft</b>
Weight per m <sup>2</sup>	<b>11 kg</b>
Weight per box	<b>20 kg</b>
Weight per box	<b>44.3 lbs</b>

#### CLASSIFICATION AND SAFETY

Supports Underfloor Heating	<b>Yes</b>
Water resistance	<b>High</b>
Fire Resistance (EN 13501)	<b>Cfl-s1</b>
Thermal conductivity (EN 12664)	<b>0,16 W/(m*K)</b>
Thermal resistance (EN 12667)	<b>0.07 m<sup>2</sup>K/W</b>
Formaldehyde emission (EN 717-1)	<b>E1 &lt;=0.1 ppm (typical value &lt;= 0.05 ppm)</b>
Brinell hardness (EN 1534)	<b>10 HB (average value)</b>
Impact resistance (EN 14354)	<b>EC3</b>
Thickness swelling (EN 14354)	<b>&lt;10% (5% typical)</b>
Wear resistance (EN 14354)	<b>&gt; 6000 cycles</b>
Slip resistance (USRV) (CEN//TS 15676)	<b>40</b>
FSC	<b>FSC Mix</b>
SundaHus	<b>Evaluated by SundaHus</b>
Svanen	<b>Yes (3029 0021)</b>
Greenguard Gold	<b>Greenguard Gold Certified</b>
A+	<b>Yes</b>
M1	<b>Yes</b>
CE Marked	<b>Yes</b>
Limited warranty (public environment)	<b>10 years</b>
Limited warranty (home environment)	<b>Limited Lifetime Warranty</b>
Level of use domestic (EN ISO 10874)	<b>Class heavy Residential (Class 23)</b>
Level of use commercial (EN ISO 10874)	<b>Class heavy commercial (Class 33)</b>



woodura®

**Bjelin Sweden AB** | [bjelin.com](http://bjelin.com) | [support@bjelin.se](mailto:support@bjelin.se) | +46-771-101099

Copyright 2024 Bjelin Sweden AB. Weights and dimensions may have minor variations depending on external circumstances. Bjelin reserves the right to deviate from the weight and dimensions in this technical data sheet. Technologies mentioned may be subject to patent protection and invented by Välinge Innovation AB ([www.valinge.se/patents](http://www.valinge.se/patents)). Use of trademarks herein owned by Bjelin Sweden AB or Välinge Innovation AB is under license.



For installation and caring instructions, and further product information, scan the QR code or visit [bjelin.com](http://bjelin.com).