

Woodura Planks 3.0

VISTORP 3.0 XL



Type of wood
Oak



Grading
Select



Surface finishing
Pro matt lacquer



Staining
Powder White



Pattern
Plank



Water resistance
High

El suelo de madera endurecida Vistorp es un suelo con acabado laca mate de tonalidad blanca con un estilo auténticamente sueco. El tono Powder White ilumina una habitación y la clasificación Select contribuye a su estética limpia y armoniosa. Fabricado con roble europeo con certificación FSC, este producto de clase 33 es extremadamente duradero e ideal para espacios de tránsito intenso, como hoteles, tiendas, oficinas y cafeterías, o la entrada de tu casa. El acabado laca mate facilita el mantenimiento del suelo y lo protege de las manchas.



Specification

GENERAL	
Type of floor	Hardened wood
Type of wood	Oak
Grading	Select
Surface finishing	Pro matt lacquer
Staining	Powder White
Light/dark	Light
Pattern	Plank
Locking system	Välinge 5G® Dry™
Core	HDF
DIMENSIONS	
Format	XL
Width	206 mm
Length	2200 mm
Thickness	11 mm
Thickness of wear layer	0,6 mm
PACKAGE	
Quantity in box	4 pcs
m² / box	1,81 m²
m² per pallet	87 m²
Weight per m²	11 kg
Weight per box	20 kg

CLASSIFICATION AND SAFETY	
Supports Underfloor Heating	Yes
Water resistance	High
Fire Resistance (EN 13501)	Cfl-s1
Thermal conductivity (EN 12664)	0,16 W/(m*K)
Thermal resistance (EN 12667)	0.07 m²K/W
Formaldehyde emission (EN 717-1)	E1 <=0.1 ppm (typical value <= 0.05 ppm)
Brinell hardness (EN 1534)	10 HB (average value)
Impact resistance (EN 14354)	EC3
Thickness swelling (EN 14354)	<10% (5% typical)
Wear resistance (EN 14354)	> 6000 cycles
Slip resistance (USRV) (CEN//TS 15676)	40
FSC	FSC Mix (FSC-C140725)
SundaHus	Evaluated by SundaHus
Greenguard Gold	Greenguard Gold Certified
A+	Yes
M1	Yes
CE Marked	Yes
Limited warranty (public environment)	10 years
Limited warranty (home environment)	Limited Lifetime Warranty
Level of use domestic (EN ISO 10874)	Class heavy Residential (Class 23)
Level of use commercial (EN ISO 10874)	Class heavy commercial (Class 33)



Bjelin bjelin.com support@bjelin.com

Copyright 2025 Bjelin Sweden AB. Weights and dimensions may have minor variations depending on external circumstances. Bjelin reserves the right to deviate from the weight and dimensions in this technical data sheet. Technologies mentioned may be subject to patent protection and invented by Välinge Innovation AB (www.valinge.se/patents). Use of trademarks herein owned by Bjelin Sweden AB or Välinge Innovation AB is under license.



For installation and caring instructions, and further product information, scan the QR code or visit bjelin.com.