

Hardened Wood 2.5

WOODURA PLANKS GULLARP
XL POWDER WHITE 2.5



Gullarp is a crisp white hardened wood floor made from ash. This Scandinavian classic in a bright Powder White color has been paired with the Select grading to lend it an even cleaner and more harmonious appearance. Gullarp is a class 31 product, which is ideal for residential areas. The matte finish makes the floor easy to maintain while protecting it from stains.



Specification

GENERAL	
Type of floor	Hardened wood
Type of wood	Ash
Grading	Select
Surface finishing	Matte finish
Staining	Powder White
Light/dark	Light
Pattern	Plank
Locking system	Välinge 5G® Dry™
Core	HDF
Level of use	Residential
DIMENSIONS	
Format	XL
Width (ISO 24337)	8.1"
Length (ISO 24337)	86.6"
Thickness (ASTM F387)	0.43"
Thickness of wear layer (ASTM F410)	0.02"
Weight per m²	24 lbs
PACKAGE	
Quantity in box	4 pcs
sq.ft per box	19.51 sqft
sq.ft per pallet	937 sqft
Weight per box	44.3 lbs

CLASSIFICATION AND SAFETY	
Supports Underfloor Heating	Yes
Water resistance	High
Fire Resistance (EN 13501)	Cfl-s1
Thermal conductivity (EN 12664)	0.16 W/(m²K)
Thermal resistance (EN 12667)	0.07 m²K/W
Formaldehyde emission (EN 717-1)	E1 <=0.1 ppm (typical value <= 0.05 ppm)
Brinell hardness (EN 1534)	10 HB (average value)
Impact resistance (EN 14354)	EC3
Thickness swelling (EN 14354)	<10% (5% typical)
Wear resistance (EN 14354)	> 6000 cycles
Slip resistance (USRV) (CEN//TS 15676)	40
FSC	FSC Mix (FSC-C140725)
Svanen	Yes (3029 0021)
Greenguard Gold	Greenguard Gold Certified
CE Marked	Yes
Warranty (commercial)	10 years
Warranty (residential)	Limited Lifetime Warranty
Level of use domestic (EN ISO 10874)	Class heavy Residential (Class 23)
Level of use commercial (EN ISO 10874)	Class light commercial (Class 31)



woodura®

Bjelin bjelin.com us-support@bjelin.com

Copyright 2025 Bjelin Sweden AB. Weights and dimensions may have minor variations depending on external circumstances. Bjelin reserves the right to deviate from the weight and dimensions in this technical data sheet. Technologies mentioned may be subject to patent protection and invented by Välinge Innovation AB (www.valinge.se/patents). Use of trademarks herein owned by Bjelin Sweden AB or Välinge Innovation AB is under license.



For installation and caring instructions, and further product information, scan the QR code or visit bjelin.com.