

Hardened Wood 2.5

WOODURA PLANKS VALLBY XL TERRA BROWN 2.5



Vallby is a striking hardened wood floor made from walnut that has a commercial matte finish. The Terra Brown shade adds depth and highlights the exquisite walnut grain while the Nature grading provides a natural color variation. This class 33 product is extremely durable and ideal for heavy-traffic spaces like hotels, shops, offices and cafés – or the entrance of your home. The commercial matte finish makes the floor easy to maintain while protecting it from stains.



Specification

GENERAL

Type of floor	Hardened wood
Type of wood	Walnut
Grading	Nature
Surface finishing	Matte finish
Staining	Terra Brown
Light/dark	Dark
Pattern	Plank
Locking system	Välinge 5G® Dry™
Core	HDF
Level of use	Residential

DIMENSIONS

Format	XL
Width (ISO 24337)	8.1"
Length (ISO 24337)	86.6"
Thickness (ASTM F387)	0.43"
Thickness of wear layer (ASTM F410)	0.02"
Weight per m ²	24 lbs

PACKAGE

Quantity in box	4 pcs
sq.ft per box	19.51 sqft
sq.ft per pallet	937 sqft
Weight per box	44.3 lbs

CLASSIFICATION AND SAFETY

Supports Underfloor Heating	Yes
Water resistance	High
Fire Resistance (EN 13501)	Bfl-S1 (hardly flammable)
Thermal conductivity (EN 12664)	0,16 W/(m*K)
Thermal resistance (EN 12667)	0.07 m ² K/W
Formaldehyde emission (EN 717-1)	E1 <=0.1 ppm (typical value <= 0.05 ppm)
Brinell hardness (EN 1534)	10 HB (average value)
Impact resistance (EN 14354)	EC3
Thickness swelling (EN 14354)	<10% (5% typical)
Wear resistance (EN 14354)	> 6000 cycles
Slip resistance (USRV) (CEN//TS 15676)	40
FSC	FSC Mix (FSC-C140725)
Greenguard Gold	Greenguard Gold Certified
CE Marked	Yes
Warranty (commercial)	10 years
Warranty (residential)	Limited Lifetime Warranty
Level of use domestic (EN ISO 10874)	Class heavy Residential (Class 23)
Level of use commercial (EN ISO 10874)	Class heavy commercial (Class 33)

MISC.

NOBB-number	60085963
-------------	----------



woodura®

Bjelin bjelin.com us-support@bjelin.com

Copyright 2025 Bjelin Sweden AB. Weights and dimensions may have minor variations depending on external circumstances. Bjelin reserves the right to deviate from the weight and dimensions in this technical data sheet. Technologies mentioned may be subject to patent protection and invented by Välinge Innovation AB (www.valinge.se/patents). Use of trademarks herein owned by Bjelin Sweden AB or Välinge Innovation AB is under license.



For installation and caring instructions, and further product information, scan the QR code or visit bjelin.com.