产品数据表| 347102

有关安装和护理说明以及进一步的产品信息，请扫
描QR码，或访问bjelin.com。

Bjelin中国 bjelin.com chinainfo@valinge.se +86 21 522 822 62

Copyright 2025 Bjelin Sweden AB. Weights and dimensions may have minor variations depending on external circumstances. Bjelin reserves the right to deviate from the weight and dimensions in this technical data sheet. Technologies mentioned may be subject to patent protection and invented by Välinge Innovation AB (www.valinge.se/patents). Use of trademarks herein owned by Bjelin Sweden AB or Välinge Innovation AB is under license.

Woodura Planks

3.0

HASSLARP 3.0 XXL

树种
橡木

分级
Nature

表面处理
专业哑光漆

颜色选择

MistyWhite

图案
常规板材

防水性
高

Hasslarp是一种看起来很干净的哑光漆硬化木地板，具有永恒的北欧风格。迷雾白的色调给房间带来了精致的感觉，创造了一种空间感，而Nature (自然)的类级则为地板设计提供了深度。这款33级产品由FSC认证的欧洲橡木制成，非常耐用，是酒店、商店、办公室和咖啡馆等人流量大地方，或您家经常走动区域的理想选择。哑光漆面使地板易于维护，同时保护其免受污浊。

规格

基础信息
地板品类 固化木地板
树种 橡木
分级 Nature
表面处理 专业哑光漆

颜色选择 MistyWhite
浅色/深色 浅色
图案 常规板材

锁扣系统 Välinge 5G™Dry™
核芯 HDF

尺寸
规格 XXL
宽 271 mm 长 2378 mm
高 11 mm
磨损层的厚度 0,6 mm

包装
箱内数量 3件
平⽅⽶/箱 1,9平方米
m² per pallet 93平方米
Weight per m² 11 kg
每箱重量 22 kg

分类和安全属性
⽀持地暖 是
防水性 高

Fire Resistance (EN 13501) Cfl-s1
Thermal conductivity (EN 12664) 0,16 W/(m*K)
Thermal resistance (EN 12667) 0.07 m²K/W Formaldehyde emission (EN 717-1) E1 <=0.1 ppm (typical value <= 0.05 ppm)
硬度等级(EN 1534) 10 HB (average value)
Impact resistance (EN 14354) EC3
Thickness swelling (EN 14354) <10% (5% typical)
Wear resistance (EN 14354) > 6000 cycles
Slip resistance (USRV) (CEN//TS 15676) 40
FSC FSC Mix
SundaHus 由SundaHus评估
Svanen 是(3029 0021)
Greenguard Gold Greenguard Gold Certified
A+ Yes
M1 Yes
CE认证 是

Limited warranty (public environment) 10年
Limited warranty (home environment) Limited Lifetime Warranty Level of use domestic (EN ISO 10874) Class heavy Residential(Class 23) Level of use commercial
(EN ISO 10874)

Class heavy commercial(Class 33)