

Woodura Planks 3.0

HASSLARP 3.0 XXL



Type of wood  
Oak



Grading  
Nature



Surface finishing  
Pro matt lacquer



Staining  
Misty White



Pattern  
Plank



Water resistance  
High


El suelo de madera endurecida Hasslarp es un suelo con acabado laca mate de estética limpia y un estilo nórdico atemporal. El tono Misty White aporta sofisticación a una habitación, creando una sensación de espacio, mientras que la clasificación Nature proporciona profundidad al diseño del suelo. Fabricado con roble europeo con certificación FSC, este producto de clase 33 es extremadamente duradero e ideal para espacios concurridos, como hoteles, tiendas, oficinas y cafeterías, o una zona muy transitada de tu casa. El acabado laca mate facilita el mantenimiento del suelo y lo protege de las manchas.



Specification

| GENERAL                 |                  |
|-------------------------|------------------|
| Type of floor           | Hardened wood    |
| Type of wood            | Oak              |
| Grading                 | Nature           |
| Surface finishing       | Pro matt lacquer |
| Staining                | Misty White      |
| Light/dark              | Light            |
| Pattern                 | Plank            |
| Locking system          | Välinge 5G® Dry™ |
| Core                    | HDF              |
| DIMENSIONS              |                  |
| Format                  | XXL              |
| Width                   | 271 mm           |
| Length                  | 2378 mm          |
| Thickness               | 11 mm            |
| Thickness of wear layer | 0,6 mm           |
| PACKAGE                 |                  |
| Quantity in box         | 3 pcs            |
| m² / box                | 1,9 m²           |
| m² per pallet           | 93 m²            |
| Weight per m²           | 11 kg            |
| Weight per box          | 22 kg            |

| CLASSIFICATION AND SAFETY              |                                          |
|----------------------------------------|------------------------------------------|
| Supports Underfloor Heating            | Yes                                      |
| Water resistance                       | High                                     |
| Fire Resistance (EN 13501)             | Cl-s1                                    |
| Thermal conductivity (EN 12664)        | 0,16 W/(m*K)                             |
| Thermal resistance (EN 12667)          | 0.07 m²K/W                               |
| Formaldehyde emission (EN 717-1)       | E1 <=0.1 ppm (typical value <= 0.05 ppm) |
| Brinell hardness (EN 1534)             | 10 HB (average value)                    |
| Impact resistance (EN 14354)           | EC3                                      |
| Thickness swelling (EN 14354)          | <10% (5% typical)                        |
| Wear resistance (EN 14354)             | > 6000 cycles                            |
| Slip resistance (USRV) (CEN//TS 15676) | 40                                       |
| FSC                                    | FSC Mix (FSC-C140725)                    |
| SundaHus                               | Evaluated by SundaHus                    |
| Svanen                                 | Yes (3029 0021)                          |
| Greenguard Gold                        | Greenguard Gold Certified                |
| A+                                     | Yes                                      |
| M1                                     | Yes                                      |
| CE Marked                              | Yes                                      |
| Limited warranty (public environment)  | 10 years                                 |
| Limited warranty (home environment)    | Limited Lifetime Warranty                |
| Level of use domestic (EN ISO 10874)   | Class heavy Residential (Class 23)       |
| Level of use commercial (EN ISO 10874) | Class heavy commercial (Class 33)        |



Bjelin   [bjelin.com](https://bjelin.com)   [support@bjelin.com](mailto:support@bjelin.com)

Copyright 2025 Bjelin Sweden AB. Weights and dimensions may have minor variations depending on external circumstances. Bjelin reserves the right to deviate from the weight and dimensions in this technical data sheet. Technologies mentioned may be subject to patent protection and invented by Välinge Innovation AB ([www.valinge.se/patents](https://www.valinge.se/patents)). Use of trademarks herein owned by Bjelin Sweden AB or Välinge Innovation AB is under license.



For installation and caring instructions, and further product information, scan the QR code or visit [bjelin.com](https://bjelin.com).