

# Woodura Planks 3.0

## NORRLIA 3.0 XXL



Norrlia er et naturlig, mattlakkert herdet tregulv i klassisk svensk design som bringer følelsen av natur inn i hjemmet. Natural-nyansen er beroligende, og Select-sorteringen skaper et rent og harmonisk uttrykk. Dette er et produkt i klasse 33 produsert av FSC-sertifisert eik. Det er ekstremt slitesterkt og ideelt for trafikkerte områder som hoteller, butikker, kontorlokaler og kafeer – eller gangen hjemme hos deg selv. Den mattlakkerte overflaten gjør gulvet enkelt å vedlikeholde og beskytter mot flekker.



### Spesifikasjon

#### GENERELT

Type gulv	<b>Herdet tregulv</b>
Treslag	<b>Eik</b>
Sortering	<b>Select</b>
Overflatebehandling	<b>Pro matt lacquer</b>
Innfarging	<b>Natural</b>
Lyst/mørkt	<b>Medium Dark</b>
Monster	<b>Plank</b>
Fug	<b>Vålinge 5G® Dry™</b>
Kjerne	<b>HDF</b>

#### MÅL

Format	<b>XXL</b>
Bredde	<b>271 mm</b>
Lengde	<b>2378 mm</b>
Høyde	<b>11,3 mm</b>
Slitesjiktets tykkelse	<b>0,6 mm</b>

#### EMBALLASJE

Antall i pakken	<b>3 stk.</b>
m <sup>2</sup> i pakken	<b>1,9 m<sup>2</sup></b>
m <sup>2</sup> per pall	<b>93 m<sup>2</sup></b>
Vekt pr. m2	<b>11 kg</b>
Vekt pr. pakke	<b>22 kg</b>

#### KLASSIFISERING OG SIKKERHET

Egnet for gulvvarme	<b>Ja</b>
Vannbestandighet	<b>Høy</b>
Motstandsdyktighet mot brann (EN 13501)	<b>Cfl-s1</b>
Termisk ledningsevne (EN 12664)	<b>0,16 W/(m<sup>2</sup>K)</b>
Termisk motstand (EN 12667)	<b>0,07 m<sup>2</sup>K/W</b>
Formaldehyd emisjon (EN 717-1)	<b>E1 ≤0,1 ppm (type verdi ≤ 0,05 ppm)</b>
Brinellhardhet (EN 1534)	<b>10 HB (average value)</b>
Slagfasthet (EN 14354)	<b>EC3</b>
Svellingsgrad (EN 14354)	<b>&lt;10% (5% type verdi)</b>
Slitestykke (EN 14354)	<b>&gt; 6000 cycles</b>
Sklisikkerhet (USRV) (CEN//TS 15676)	<b>40</b>
FSC	<b>FSC Mix</b>
SundaHus	<b>Bedømt av SundaHus</b>
Svanen	<b>Ja (3029 0021)</b>
Greenguard Gold	<b>Greenguard Gold Certified</b>
A+	<b>Yes</b>
M1	<b>Yes</b>
CE-merket	<b>Ja</b>
Garanti (offentlige miljø)	<b>30 år</b>
Garanti (private hjem)	<b>30 år</b>
Slitestykke i private hjem (EN ISO 10874)	<b>Moderat til sterkt trafikkerte områder (klasse 23)</b>
Slitestykke i offentlige miljø (EN ISO 10874)	<b>Høytrafikkområder (klasse 33)</b>
ANNEK	
NOBB-nummer	<b>60085928</b>



woodura®

**Bjelin** bjelin.com support@bjelin.com +47 3322 2300

Copyright 2024 Bjelin Sweden AB. Weights and dimensions may have minor variations depending on external circumstances. Bjelin reserves the right to deviate from the weight and dimensions in this technical data sheet. Technologies mentioned may be subject to patent protection and invented by Välinge Innovation AB (www.valinge.se/patents). Use of trademarks herein owned by Bjelin Sweden AB or Välinge Innovation AB is under license.



Skann QR-koden med mobilen eller besøk [bjelin.com](http://bjelin.com) for å se informasjon om legging og ytterligere produktinformasjon.